Notes on H2 Physics

Ma Weiyi

ma.weiyi@dhs.edu.sg

These notes review the H2 Physics (9749) syllabus. Updated April 20, 2025.

Contents

Ι	Measurement	5
1	Measurements 1.1 Physical Quantities 1.2 Scalars & Vectors 1.3 Errors & Uncertainties 1.4 Propagation of Uncertainties	6 6 7 9
Π	I Newtonian Mechanics	10
2	Kinematics	11
	2.1 Translational Kinematic Quantities	11
	2.2 Graphical Methods	12
	2.3 Equations of Motion	12
	2.4 Motion Under Gravity	13
	2.5 Non-Linear Motion	13
~		
3		16
	3.1 Mass, Weight, & Momentum	10
	3.2 Newton's Laws of Motion	10
	3.3 Common Mechanical Forces	10
	3.4 Free-Dody Diagrams	- 19 - 99
	5.5 Conservation of Linear Momentum	
4	Forces	24
	4.1 Conservative Forces	24
	4.2 Dissipative Forces	24
	4.3 Center of Gravity	25
	4.4 Hooke's Law	25
	4.5 Upthrust	26
	4.6 Static Equilibrium	27
5	Work Energy & Power	30
0	5.1 Work	30
	5.2 Fnerov	30
	5.3 Conservation of Mechanical Energy	32
	5.4 Power	32
6	Motion in a Circle	34
	0.1 Kadlans	34
	b.2 Angular Velocity c.2 Contributed	34
	b.3 Centripetal Acceleration	35
	0.4 Centripetal Force	35
	0.5 Turning Motion OF venicies	
	0.0 vertical Orcular Motion	

7	Gravitatio	nal Fields																39
	7.1 Newto	n's Law of Gravitation	 															39
	7.2 Gravit	ational Field	 															39
	7.3 Gravit	ational Potential Energy .	 															41
	7.4 Energy	Considerations	 															42
	7.5 Kepler	's Third Law	 															43
	7.6 Geosta	tionary Orbits	 															44
		0																
II	I Therma	l Physics																45
8	Temperate	re and Ideal Gases																46
	8.1 Zeroth	Law of Thermodynamics.	 															46
	8.2 Tempe	rature Scales	 															46
	8.3 Ideal (fas Law	 															47
	8.4 Kineti	Theory of Gases	 															48
		U																
9	First Law	of Thermodynamics																51
	9.1 Intern	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	 • •	• •	• • •	•	•••	• •	•	•••	•••	• •	•	• •	·	•••	•	51
	9.2 Heat 0	Japacity	 • •	• •	•••	•	•••	• •	•	•		• •	•		•		•	51
	9.3 First I	aw of Thermodynamics	 • •	• •	•••	•		• •	•	• •	• •	• •	•	•••	•		•	52
IV	/ Oscillat	ions and Waves																54
10																		
10	10.1 E	.S																55
	10.1 Free C	scillations \dots \dots \dots	 • •	• •	•••	•	•••	• •	•	•••		• •	•	•••	·	•••	•	55 50
	10.2 Simple	Harmonic Motion	 • •	• •	• • •	•	•••	• •	•	• •	•••	• •	•	•••	·	•••	•	00 60
	10.3 Damp	Occillations	 • •	• •	• • •	•	•••	• •	•	• •	•••	• •	•	•••	·	•••	•	00 61
	10.4 Forced	Oscillations	 • •	• •		•	•••	• •	• •	•••		• •	•	• •	·	•••	•	01
11	Wave Mot	ion																63
	11.1 Waves		 			•												63
	11.2 Catho	le Ray Oscilloscope	 			•							•					66
	11.3 Intens	ty	 			•												66
	11.4 Polaris	ation	 			•			• •	•••			•		•			68
12	Superposi	ion																69
	12.1 Superi	position Principle	 															69
	12.2 Interfe	rence	 	• •		•	•••	• •	•		•••	• •	•		•	•••	•	69
	12.3 Statio	ary Waves	 • •	• •		•	•••	• •	•		•••	• •	•		•	•••	•	70
	12.9 Diation	tion	 •••	• •	•••	•	•••	• •	• •	•••		• •	•	•••	•	•••	•	72
	12.4 Dima		 •••	• •	•••	•	•••	• •	• •	•••	•••	• •	•	•••	•	•••	•	12
\mathbf{V}	Electrici	ty and Magnetism																75
13	Electric F	elds																76
	13.1 Electr	c Force	 															76
	13.2 Electr	c Field	 			-				•			•					76
	13.3 Electric	c Potential .	 			•				•			•					80
	13.4 Electr	c Potential Energy	 							•	• • •		•					81
	-	0.																

14 Current of Electricity												83
14.1 Charge		 	 			 		•				83
14.2 Electric Current		 	 			 		•				83
14.3 Voltage \ldots \ldots \ldots		 	 			 						84
14.4 Resistance \ldots \ldots \ldots		 	 			 						85
14.5 Electrical Power		 	 			 						88
14.6 Internal Resistance		 •••	 	•••	•••	 	•	•	 •	•	 •	88
15 D.C. Circuits												91
15.1 Symbols \ldots \ldots \ldots		 	 			 		•				91
15.2 Kirchhoff's Laws		 	 			 						91
15.3 Effective Resistance		 	 			 						93
15.4 Potential Divider		 	 			 		•				93
15.5 Potentiometer \ldots \ldots \ldots		 •••	 	•••	•••	 	•	•	 •	•	 •	94
16 Electromagnetism												98
16.1 Magnetic Fields		 	 			 						98
16.2 Magnetic Flux Density		 	 			 		•				100
16.3 Magnetic Force \ldots \ldots \ldots		 •••	 		•••	 	•	•	 •	•	 •	100
17 Electromagnetic Induction												104
17.1 Magnetic Flux		 	 			 		•				104
17.2 Faraday's Law		 	 			 		•				104
17.3 Lenz's Law		 	 			 		•				105
17.4 Motional Electromotive Fore	e	 	 			 		•				106
17.5 Generators \ldots \ldots		 	 			 		•				107
17.6 Eddy Currents \ldots \ldots		 	 	•••		 	•	•	 •	•		108

Part I Measurement

1 Measurements

1.1 Physical Quantities

Definition 1.1: Quantity

A **physical quantity** is any scientifically measurable quantity (e.g. temperature, force, mass). All physical quantities consist of a **numerical value** and a **unit**.

A **base quantity** is one of the seven physical quantities of the S.I. system by which all other physical quantities are defined.

A **derived quantity** is a physical quantity that can be expressed in terms of products and quotients of base quantities.

The seven base quantities, along with their S.I. units, are shown below.

Base quantity	Base unit	Symbol
Mass	kilogram	kg
Length	metre	m
Time	second	s
Electric current	ampere	А
Thermodynamic temperature	kelvin	К
Amount of substance	mole	mol
Luminous intensity	candela	cd

Base units can be used to **check the dimensional homogeneity** of a physical equation. If the units of each term are equal on both sides of the equation, the equation is said to be **homogenous** or dimensionally constant.

Quantities use prefix to indicate decimal sub-multiples or multiples.

1.2 Scalars & Vectors

Definition 1.2: Scalars & Vectors

A scalar is a quantity has magnitude but no direction. It is completely specificed by its numerical value and unit.

A **vector** is a quantity that has **both** magnitude and direction. It must be specified with its value, unit, and direction.

The **change** in a certain physical quantity $\vec{\mathbf{Q}}$ can simply be taken as the subtraction between its final and initial state.

$$\Delta \mathbf{Q} = \mathbf{Q}_f - \mathbf{Q}_i$$

10^n	Prefix	Symbol	Name
$10^{1}2$	tera	Т	trillion
109	giga	G	billion
10^{6}	mega	М	million
10^{3}	kilo	k	thousand
100	-	-	one
10^{-1}	deci	d	tenth
10^{-2}	centi	с	hundredth
10^{-3}	milli	m	thousandth
10^{-6}	micro	μ	millionth
10^{-9}	nano	n	billionth
10^{-12}	pico	p	trillionth

Since two vectors can be added to give a resultant vector, any vector can be resolved into two constituent vectors.

Vectors can be resolved into two mutually perpendicular, independent components through trigonometry. Given a vector $\vec{\mathbf{A}}$ with magnitude $|\vec{\mathbf{A}}|$ inclined at an angle θ from the positive x-axis, its corresponding x and y components are given as:

$$A_x = |\mathbf{A}| \cos \theta, \qquad A_y = |\mathbf{A}| \sin \theta$$

1.3 Errors & Uncertainties

Definition 1.3: Uncertainty

Uncertainty is the range of values of a measurement in which the actual value of the measurement is expected to lie within, commonly arising from (1) limitations of the observer, (2) limitations of the apparatus, and/or (3) limitations of the method.

Definition 1.4: Error

Error is the difference between the measured value and the true value.

Systematic errors are present when the measured values produce errors of the same magnitude and sign. They cannot be eliminated by averaging, but can be reduced through careful design of experimental processes.

Random errors are present when the measured values produce errors of different magnitudes and signs. These readings are scattered about the **mean value** with no fixed pattern.

As described, errors can be differentiated into systematic errors and random errors.



1.3.1 Precision & Accuracy

Definition 1.5: Precision

The **precision** of a measurement refers to how close the experimental values are to each other.

Precision describes the level of uncertainty in an instrument's scale. Good precision indicates small random errors.

Definition 1.6: Accuracy

Accuracy is the closeness of a reading on an instrument to the true value of the quantity being measured.

Good accuracy indicates small systematic errors.



1.3.2 Uncertainty

In a scale reading, the **absolute uncertainty** is half of its smallest division, rounded off to 1 significant figure. In general, all readings can be recorded in the form $R \pm \Delta R$, where ΔR is the absolute uncertainty.

The uncertainty of a measured value can also be presented as a percent or a simple fraction. The **fractional** uncertainty of R is $(\Delta R)/R$, whereas its **percentage** uncertainty is $(\Delta R)/R \times 100\%$.

The absolute uncertainty (with units, 1 s.f.) indicates the **scale sensitivity** of the measuring instrument used. The percentage uncertainty (dimensionless, 2 s.f.) is useful to compare the **significance of the error**.

1.4 Propagation of Uncertainties

Consequential uncertainty is the overall estimate of uncertainty throughout an entire experiment. To statistically calculate consequential uncertainty, we consider **maximum uncertainty**, which occurs in the worst-case scenario.

Let A and B be measured independent quantities, with ΔA and ΔB being their corresponding uncertainties. The following rules will apply for a derived quantity Z.

$$Z = mA + nB \implies \Delta Z = |m|\Delta A + |n|\Delta B$$
$$Z = A^m \times B^n \implies \frac{\Delta Z}{Z} = |m|\frac{\Delta A}{A} + |n|\frac{\Delta B}{B}$$

When adding or substracting measurements, add their absolute uncertainties. When multiplying or dividing measurements, add their fractional uncertainties. If a quantity A is being divided by k, simply regard it as a multiplication of k^{-1} .

For complicated functions, it is acceptable to calculate the maximum uncertainty as the median value between the range of possible quantities.

$$\Delta Z = \frac{1}{2}(Z_{\rm max} - Z_{\rm min})$$

Part II Newtonian Mechanics

2 Kinematics

2.1 Translational Kinematic Quantities

Definition 2.1: Distance

Distance, d, is the total length of path covered by a moving object irrespective of the direction of motion. It is a scalar quantity.

Definition 2.2: Displacement

Displacement, denoted by \vec{s} , is the linear distance of the position of a moving object from a given reference point. It is a vector quantity.

Definition 2.3: Speed

Speed is the distance travelled per unit time. It is a scalar quantity.

The **average speed**, $\langle u \rangle$, is the ratio of total distance travelled to the time interval during which a particle travels over that distance.

$$\langle u \rangle = \frac{d}{t}$$

Definition 2.4: Velocity

Velocity, denoted by $\vec{\mathbf{v}}$, is the rate of change of displacement with time, acting in the direction of change of displacement. It is a vector quantity.

The **average velocity**, $\langle v \rangle$, is the ratio of displacement to the time interval during which the displacement occurs.

$$\langle v \rangle = \frac{s}{t}$$

Instantaneous velocity is defined as the limit of the average velocity as the time interval Δt becomes infinitesimally short. This is mathematically formulated below.

$$v = \lim_{\Delta t \to 0} \frac{\Delta s}{\Delta t} = \frac{ds}{dt}$$

Definition 2.5: Acceleration

Acceleration, denoted by \vec{a} , is the rate of change of velocity with time.

Acceleration is a *vector quantity* that acts in the direction of the change of velocity. An object is said to be accelerating if its velocity is changing, either in magnitude or direction.

Average acceleration is the ratio of the change in velocity over the time interval for which this change occurs.

$$\langle a \rangle = \frac{\Delta v}{\Delta t}$$

Instantaneous acceleration is the limit of average acceleration as the time interval goes to zero.

$$a = \lim_{\Delta t \to 0} \frac{\Delta v}{\Delta t} = \frac{dv}{dt}$$

2.2 Graphical Methods

2.2.1 Displacement-Time Graphs

The displacement of any object can be represented using a displacement-time graph, which expresses how displacement changes with time.

Since $v = \frac{ds}{dt}$, the velocity at any instant can be found from the gradient of the displacement-time graph.



The ratio $\frac{\Delta s}{\Delta t}$ shown on the left graph gives the magnitude of the **average velocity**, $\langle v \rangle$, for the time interval Δt .

The instantaneous velocity at Q, shown on the right graph, is found by finding the gradient of the tangent at point Q.

2.2.2 Velocity-Time Graphs

We can also represent the motion of an object using a velocity-time graph.

If two bodies have positions at times (x_1, t_1) and (x_2, t_2) respectively, the displacement Δx during a small time interval Δt is equal to $\langle v \rangle_x \Delta t$, where $\langle v \rangle_x$ is the average x-velocity during Δt . The total displacement $x = x_2 - x_1$ during the interval $[t_1, t_2]$ is thus given by

$$x_2 - x_1 = \int_{x_1}^{x_2} dx = \int_{t_1}^{t_2} v_x \, dt$$

The displacement is the **time integral** of x-velocity V_x . Graphically, the displacement between a time interval is the **area under the** v_x -t curve within that time interval.

Since $a = \frac{dv}{dt}$, the acceleration at any instant can be found from the gradient of the velocity-time graph.

2.3 Equations of Motion

Consider a particle moving with constant acceleration, a, in a straight line. Let u be the initial velocity, v be the final velocity, t be the time taken, and s be the displacement along a straight line.

The kinematic equations of motions in such a situation are

$$v = u + at$$

$$s = 0.5(u + v)t$$

$$s = ut + 0.5at^{2}$$

$$s = vt - 0.5at^{2}$$

$$v^{2} = u^{2} + 2as$$

The equations of motion are vector equations, thus possessing magnitude and direction. For all rectilinear vector problems, directions are indicated using positive and negative signs.

If we take the direction towards our right as positive, then the direction towards our left will be negative.

2.4 Motion Under Gravity

2.4.1 Negligible Air Resistance

Consider scenarios where the only force acting on the ball is gravity. After time t, the velocity of the ball released from rest would be given by

$$v = u + at$$

= gt (since $u = 0$)

2.4.2 Air Resistance

Air resistance opposing motion tends to increase approximately with the square of the speed at high velocities and increase proportionately with speed at low velocities.

The larger the velocity, the greater the air resistance. The actual acceleration is the combined free-fall acceleration and the retardation due to air resistance.

Taking downward as positive, where F_R represents air resistance,

$$F = ma = mg - F_R$$
$$\therefore a = g - \frac{F_R}{m}$$

For bodies falling from great heights, the air resistance can be very large, to the point where $F_R = mg$. Here, F = 0N, and the body has reached **terminal velocity**, v_T .

2.5 Non-Linear Motion

Non-linear motion deals with objects moving in a two-dimensional plane, as opposed to straight-line paths. Bodies undergoing projectile motion experience uniform velocity in one direction and a uniform acceleration in a perpendicular direction.

When an object is thrown into the air at an angle θ with respect to the ground with speed v, the body will move in a parabolic path.

The velocity of the projectile at any time is given by the vector sum of v_x and v_y at that time.

$$v = \sqrt{v_x^2 + v_y^2}$$



To ascertain the angle of direction,

$$\theta = \tan^{-1} \frac{v_y}{v_x}$$

2.5.1 Horizontal Motion

Horizontally, the body is moving with a **constant velocity**. There is no resultant force, hence the horizontal acceleration is **zero**.

$$a_x = 0$$

$$v_x = u_x + a_x t = u_x$$

$$s_x = u_x t + 0.5a_x t^2 = u_x t$$

2.5.2 Vertical Motion

Vertically, the body moves under the influence of gravity with a **constant acceleration** (of g), causing the velocity to change with time.

Taking downwards as positive,

$$egin{aligned} & a_y = g \ & v_y = u_y + gt \ & s_y = u_y t + 0.5gt^2 \end{aligned}$$

The following equation is time-independent.

$$v_y^2 = u_y^2 + 2gs_y$$

2.5.3 Maximum Height

Note that at the maximum height, $v_y = 0$. Taking the time-independent equation,

$$v_y^2 = u_y^2 + 2gs_y \implies v_y^2 (u\sin\theta)^2 - 2gH$$

$$\implies H = \frac{u^2\sin^2\theta}{2g}$$

To determine the time taking to reach the maximum height,

$$v_y = u_y + a_y t \implies u \sin \theta - g t_{up}$$

 $\implies t_{up} = \frac{u \sin \theta}{g}$

2.5.4 Total Time of Flight

As the trajectory is a parabola, the time taken to travel upwards is equal to the time taken to travel downwards. Therefore,

$$t_{up} = t_{down} \implies T = 2t_{up}$$

 $\implies T = \frac{2u\sin\theta}{g}$

2.5.5 Range

The maximum horizontal distance covered by the projectile is known as the **horizontal range**, R.

$$R = v_x T = (u \cos \theta) \frac{2u \sin \theta}{g}$$
$$\implies \boxed{R = \frac{u^2 \sin 2\theta}{g}}$$

For a given speed of projection, u, the horizontal range is maximum when $\sin 2\theta = 1 \Rightarrow \theta = 45^{\circ}$. Thus, the maximum range is

$$R_{\max} = \frac{u^2}{g}$$

3 Dynamics

3.1 Mass, Weight, & Momentum

Definition 3.1: Mass

Mass is the amount of matter in a body. It is a scalar quantity with S.I. unit kg.

Consequently, mass is the measure of inertia in the body — the **inertia** of a body is the reluctance of the body to start moving, and to stop once it has begun moving.

The larger the mass of a body, the larger its inertia.

Definition 3.2: Weight

Weight is defined as the **force** acting on a body due to **gravity**. For any given non-massless body,

 $\vec{\mathbf{W}} = m\vec{\mathbf{g}}$

where $\vec{\mathbf{W}}$ is the weight of the body, *m* is the mass of the body, and $\vec{\mathbf{g}}$ is the acceleration due to gravity.

The mass of an object is constant irrespective of space, but its weight is a **force** with a magnitude dependent on the value of g.

An object's weight on the Moon is a fraction of that on Earth, due to the Moon's weaker force of gravity. Nonetheless, it retains its inertia, as the mass is the same.

Definition 3.3: Linear Momentum

Linear momentum of a body is the product of its mass and velocity.

 $\vec{\mathbf{p}}=m\vec{\mathbf{v}}$

where $\vec{\mathbf{p}}$ is the momentum, *m* is the mass, and $\vec{\mathbf{v}}$ is the velocity of the body.

Momentum is a vector quantity acting in the same direction as velocity. The S.I. unit of momentum is N s.

3.2 Newton's Laws of Motion

Definition 3.4: Newton's First Law

Newton's first law of motion states that a body continues in its state of rest or uniform motion in a straight line, unless a resultant external force acts on it.

This law implies that

- 1. the **state of rest** requires no resultant force to maintain;
- 2. the state of uniform velocity also requires no resultant force to maintain.

Definition 3.5: Newton's Second Law

Newton's second law of motion states that the rate of change of momentum of a body is proportional to the resultant force acting on it, and occurs in the direction of the resultant force.

From the above definition, we see that

$$\sum \vec{\mathbf{F}} \propto \frac{d\vec{\mathbf{p}}}{dt} \implies \sum \vec{\mathbf{F}} = k \frac{d\vec{\mathbf{p}}}{dt}$$

where k is the constant of proportionality.

The S.I. unit force is the newton (N). One newton is defined as the force which produces an acceleration of 1m/s^2 when applied to a mass of 1kg, thus conveniently setting k = 1.

$$\sum \vec{\mathbf{F}} = \frac{d\vec{\mathbf{p}}}{dt} = \frac{d(m\vec{\mathbf{v}})}{dt}$$
$$= m\frac{d\vec{\mathbf{v}}}{dt} + \vec{\mathbf{v}}\frac{dm}{dt}$$

When **mass** is constant,

$$\sum \vec{\mathbf{F}} = m \frac{d\vec{\mathbf{v}}}{dt} = m\vec{\mathbf{a}}$$

When **velocity** is constant,

$$\sum \vec{\mathbf{F}} = \vec{\mathbf{v}} \frac{dm}{dt}$$

A direct result of Newton's Second Law is the **impulse-momentum theorem**. Here, we define the impulse of a force and formulate the impulse-momentum theorem.

Definition 3.6: Impulse

The **impulse of a force** is defined as the time integral of a force during which the force is acting on an object.

$$\vec{\mathbf{I}} = \int_{t_i}^{t_f} \sum \vec{\mathbf{F}} \, dt$$

Definition 3.7: Impulse-Momentum Theorem

The **impulse-momentum theorem** states that the impulse of a force acting on an object is equal to the **change** in the momentum of the object.

$$\int_{t_i}^{t_f} \sum \vec{\mathbf{F}} \, dt = \Delta \vec{\mathbf{p}} = \vec{\mathbf{p}}_f - \vec{\mathbf{p}}_i$$

Proof. From Newton's Second Law,

$$\vec{\mathbf{F}} = \frac{d\vec{\mathbf{p}}}{dt} \implies \vec{\mathbf{F}}dt = d\vec{\mathbf{p}}$$
$$\implies \int_{t_i}^{t_f} \vec{\mathbf{F}} dt = \int_{\vec{\mathbf{p}}_i}^{\vec{\mathbf{p}}_f} d\vec{\mathbf{p}} = \vec{\mathbf{p}}_f - \vec{\mathbf{p}}_i = \Delta \vec{\mathbf{p}}$$

The extent to which the momentum of a body is changed by a given net force depends on the magnitude of the net force, and the duration for which the force acts on the body.

Definition 3.8: Newton's Third Law

Newton's third law of motion states that if a body A exerts a force on a body B, then body B exerts an equal but opposite force on body A.

$$F_{AB} = -F_{BA}$$

where F_{AB} is the force that A exerts on B, and F_{BA} is the force that B exerts on A.

3.3 Common Mechanical Forces

We discuss mechanical forces that are commonly considered when drawing free-body diagrams.

3.3.1 Normal Force

The **normal force** is the **contact** force that acts perpendicular to the surface between two objects. When we are standing on the ground, the normal force on us due to the ground opposes the gravitational force and prevents us from accelerating to the Earth's core.

3.3.2 Friction

Between any two surfaces in contact, there will always be a normal force (perpendicular to the interface) and a frictional force (parallel to the interface).



Static friction, $\vec{f_s}$, is always directed to oppose the relative impending motion.

$$f_s \le \mu_s n$$

where μ_s is the coefficient of the static frictional force.

Kinetic friction, $\vec{\mathbf{f}}_k$, is always directed to oppose the relative motion.

$$f_k = \mu_k n$$

where μ_k is the coefficient of the kinetic frictional force.



Values of μ_s and μ_k depend on the nature of the surfaces, but μ_k is generally less than μ_s . μ_s and μ_k are nearly independent of the area of contact.

3.3.3 Tension

Tension is the force exerted by a rope when pulled on. Every piece of the rope feels a tension force in both directions, except for the endpoints, which feel a tension on one side and a separate force by the object on the other.

Note that in most cases, ropes are assumed to be **massless**, hence the **tension must be the same at all points**. Otherwise, this would yield a net force, consequently resulting in infinite acceleration.

3.4 Free-Body Diagrams

When considering problems, it is helpful to draw a free-body diagram with the following procedure:

- 1. Isolate the system in question.
- 2. Identify all external forces acting on the system and draw them as vectors as appropriate points on the system.

Then, follow the general procedure for solving.

- 1. Consider **various systems** and their free-body diagrams. To choose systems, examine the forces that you need to solve. If they do not include internal forces (e.g. friction, normal forces between surfaces), consider **paired objects** as a **whole system**. Otherwise, segregate the objects.
- 2. Write the $\sum \vec{\mathbf{F}} = m\vec{\mathbf{a}}$ equations for all considered systems.
- 3. If necessary, identify certain relationships between variables to formulate additional equations.

Example 3.1

A man of mass m is in a lift undergoing an acceleration a upwards. Find the normal force exerted on the man by the floor of the lift.

We start by drawing a free-body diagram.



From Newton's Second Law, we obtain

$$N - mg = ma \implies N = m(a + g)$$

Example 3.2

A person stands on a platform-and-pulley system known as a **Bosun's chair**. The masses of the platform, person, and pulley are M, m, and μ respectively. The rope is massless. Let the person pull up on the rope so that she has acceleration a upward. Find the tension of the rope, the normal force between the person and the platform, and the tension in the rod connecting the pulley to the platform.



To find the tension in the rope, consider the whole system (except the ceiling). The only forces acting on this system are the three weights $(Mg, mg \text{ and } \mu g)$ and the tension T.

$$T - (M + m + \mu)g = (M + m + \mu)a \implies T = (M + m + \mu)(g + a)$$

To find the normal force N between the person and he platform, and also the tension f in the rod connecting the pulley to the platform, we must consider subsystems.

Applying Newton's 2nd law to the person (experiencing gravity, normal force, and tension),

$$N - T - mg = ma$$

Applying Newton's 2nd law to the platform (gravity, normal force, and force upward from the rod),

$$f - N - Mg = Ma$$

Applying Newton's 2nd law to the pulley (gravity, force downward from the rod, and twice the tension in the rope),

$$2T - f - \mu g = \mu a$$

From these equations, we can deduce

and

$$f = (2M + 2m + \mu)(g + a)$$

 $N = (M + 2m + \mu)(g + a)$

Example 3.3

Consider the pulley system below, termed an **Atwood's machine**, with masses m_1 and m_2 . The strings and pulleys are massless. Solve for the accelerations of the masses and the tensions of the strings.



Firstly, since the strings are massless, tension must be constant throughout (otherwise infinite acceleration occurs).

 $T_1 = T_2$

Applying Newton's 2nd law,

$$T - m_1 g = m_1 a$$
$$T - m_2 g = m_2 a$$

The final equation relating a_1 to a_2 is the "conservation of string". If we move the m_2 pulley upwards by a distance d, the m_1 pulley has to go down a distance d. This applies to acceleration as well.

$$a_1 = -a_2$$

Thus, this gives

$$T = \frac{2m_1m_2}{m_1 + m_2}g$$
$$a_1 = \frac{m_1 - m_2}{m_1 + m_2}g$$
$$a_2 = \frac{m_2 - m_1}{m_1 + m_2}g$$

3.5 Conservation of Linear Momentum

Definition 3.9: Principle of Conservation of Linear Momentum

The **principle of conservation of linear momentum** states that the total momentum of a system **remains constant**, provided that **no** net external resultant force acts on the system.

Consider a mass m_A travelling with velocity u_A that collides with mass m_B with velocity u_B . During the collision, the two masses are in contact and exert a force F on each other. The duration of impact is Δt .

By Newton's 2nd Law,

$$F_{AB} = \frac{\Delta p_B}{\Delta t} = \frac{m_B v_B - m_B u_B}{\Delta t}$$
$$F_{BA} = \frac{\Delta p_A}{\Delta t} = \frac{m_A v_A - m_A u_A}{\Delta t}$$

By Newton's 3rd Law,

$$F_{AB} = -F_{BA}$$

$$\frac{m_B v_B - m_B u_B}{\Delta t} = -\frac{m_A v_A - m_A u_A}{\Delta t}$$

$$m_A u_A + m_B u_B = m_A v_A + m_B v_B$$

 \therefore total initial momentum = total final momentum

With this principle in mind, we may examine two main types of collisions between bodies — elastic collisions and inelastic collisions.

In elastic collisions, the **total momentum and kinetic energy is conserved**. As such, the relative velocity of approach is equal to the relative velocity of separation.

In inelastic collisions, only the total momentum is conserved. The **total kinetic energy is not conserved**.

3.5.1 Elastic Collisions

Consider two spheres, A and B with respective masses m_A and m_B , colliding elastically with each other. The initial velocities of A and B are u_A and u_B respectively. After the collision, A and B move off with velocities v_A and v_B respectively.

By the conservation of momentum,

$$m_A u_A + m_B u_B = m_A v_A + m_B v_B$$

By the conservation of kinetic energy,

$$\frac{1}{2}m_A u_A{}^2 + \frac{1}{2}m_B u_B{}^2 = \frac{1}{2}m_A v_A{}^2 + \frac{1}{2}m_B v_B{}^2$$

Following from this,

$$m_A(u_A - v_A) = m_B(v_B - u_B)$$
 (from COM)

$$m_A(u_A + v_A)(u_A - v_A) = m_B(v_B + u_B)(v_B - u_B)$$
 (from COKE)

$$\implies u_A + v_A = v_B + u_B$$

$$\therefore u_A - u_B = v_B - v_A$$

This shows us that for elastic collisions, the **relative velocity of approach is equal to the relative velocity of separation** in terms of magnitude. Consequently, we may derive the closedform expressions for the final velocities for each body.

$$v_1 = \frac{m_A - m_B}{m_A + m_B} u_A + \frac{2m_B}{m_A + m_B} u_B$$
$$v_2 = \frac{2m_A}{m_A + m_B} u_A + \frac{m_B - m_A}{m_A + m_B} u_B$$

From these results, we may highlight expected behaviour in special, notable situations.

If two identical masses collide, they exchange velocities after the collision.

$$v_1 = u_2$$
 and $v_2 = u_1$

If an extremely big mass, m_1 , collides with a very small mass at rest, m_2 (i.e. $m_1 >> m_2$ and $v_2 = 0$), the big mass continues with a speed close to its initial speed, while the small mass bounces off with a speed about twice the initial speed of m_1 .

$$v_1 \approx u_1$$
 and $v_2 \approx 2u_1$

If a very small mass, m_1 , collides with a very big mass at rest (i.e. $m_2 >> m_1$ and $v_2 = 0$), the small mass rebounds with a speed close to its initial speed, and the big mass remains almost stationary.

 $v_1 \approx -u_1$ and $v_2 \approx 0$

3.5.2 Inelastic Collisions

In realistic collisions, change in kinetic energy take place although the momentum of the system is still conserved. This loss in kinetic energy is due to the increase in internal energy and heat dissipated to the surroundings.

For inelastic collisions,

1. total momentum is conserved;

$$m_A u_A + m_B u_B = m_A v_A + m_B v_B$$

2. and total kinetic energy is not conserved.

$$\frac{1}{2}m_A u_A{}^2 + \frac{1}{2}m_B u_B{}^2 \neq \frac{1}{2}m_A v_A{}^2 + \frac{1}{2}m_B v_B{}^2$$

For **perfectly inelastic collisions**, the two bodies will coalesce post-collision, moving off together with a common velocity.

 $v_1 = v_2$

4 Forces

4.1 Conservative Forces

A **force** is defined as the rate of change of momentum of a free-moving object. The direction of the force is in the direction of the change of momentum.

A force is **conservative** if the work it does on an object moving between two points is **independent** of the path the object takes.

Conversely, a force is **non-conservative** if the work it does on an object depends on the path taken by the object between its endpoints.

For instance, gravity is a conservative force, while friction is a non-conservative force.

4.2 Dissipative Forces

Friction and viscous forces are known as dissipative forces.

Some energy of the object moving through the fluid is **dissipated as heat** to the surroundings.

4.2.1 Friction

Definition 4.1: Frictional Force

Frictional force is the force exerted by one body on another body when two bodies slide over one another.

It is caused by irregularities in the surfaces in mutual contact and depends on the surfaces in contact as well as how much they are pressed against each other. It is the **component of contact** force along surface of contact.

Even the flattest and most highly polished surface have hollows and humps more than one hundred atoms high — when one solid is placed over one another, contact occurs only at a few places of small areas. The pressure at the points of contact is extremely high and causes the humps to flatten out until the increased area of contact enables the upper solid to be supported.

At the points of contact, small, cold-welded "joints" are formed by the strong adhesive forces between molecules which are very close together. These joints have to be broken before one surface can move over the other, giving way to **static friction**.

4.2.2 Viscous Drag

Definition 4.2: Drag

Viscous drag is the frictional force experienced either by an object as it moves through a fluid or by a fluid as it moves over a surface.

The magnitude of drag **increases** as the speed of the object increases.

4.3 Center of Gravity

Every particle of mass is attracted towards the centre of the earth by force of gravity.

The weight of a body may be taken as acting at a single point, known as its centre of gravity (hereafter termed C.G.).

The C.G. of a homogeneous, symmetric body must lie on its axis of symmetry.

4.4 Hooke's Law

Definition 4.3: Hooke's Law

Hooke's law states that the change in length e of a material is directly proportional to the resultant force F applied, provided the limit of proportionality has not been exceeded. For the given diagram,



where

- F is the force applied to the material
- L_0 is the unstretched length of material
- L is the final length of material
- x is the extension of the material, where $e = L L_0$
- k is the proportionality constant

Assuming that a material obeys Hooke's law, the force applied is **linearly proportional** to the extension of the material. This law applies to springs, as well as metals in the form of wires.

For a number of spring constants k_1, k_2, \dots, k_n that are connected in parallel, they can be replaced by a single spring constant.

$$k_{\text{eff}} = k_1 + k_2 + \dots + k_n = \sum_{i=1}^n k_i$$

For a number of spring constants k_1, k_2, \dots, k_n that are connected in parallel, they can be replaced by a single spring of constant

$$k_{\text{eff}} = \frac{1}{k_1} + \frac{1}{k_2} + \dots + \frac{1}{k_n} = \left(\sum_{i=1}^n \frac{1}{k_i}\right)^{-1}$$

4.4.1 Elastic Potential Energy

Definition 4.4: Elastic Potential Energy

The elastic potential energy stored in a deformed material obeying Hooke's law can be found from the area under a force-extension graph.

$$U = \frac{1}{2}Fx = \frac{1}{2}kx^2 = \frac{F^2}{2k}$$

An external force F_{ext} acting on a wire causing it to extend from x_1 to x_2 performs work given by

$$W = \int_{x_1}^{x_2} F_{\text{ext}} \, dx$$

This work is stored as **elastic potential energy** in the wire. The elastic potential energy is equal to the area under the force-extension curve, between the limits of x_1 and x_2 .

4.5 Upthrust

Definition 4.5: Upthrust

Upthrust is the **net upward force** exerted by the surrounding fluid when a body is **submerged fully or partially** in a fluid.

It is the resultant force due to the difference in pressure exerted by the fluid at the top and bottom surfaces of the body. It is equal in magnitude to the weight of fluid displaced by the body.

Definition 4.6: Archimedes's Principle

Archimedes's Principle states that for any object immersed partially or fully in a fluid, the upthrust is equal in magnitude and opposite in direction to the weight of fluid displaced by the object.

 $U = W_{\text{fluid displaced}} = m_f g = \rho_f g V_{\text{fluid displaced}}$

Proof. Consider a solid cylinder of height h and cross-sectional area A, submerged in a fluid of density ρ .



Recall that pressure is force over area.

$$p = \frac{F}{A}$$

Hence, the pressure of the top surface is given by

$$p_{\text{top}} = \frac{\text{weight of fluid}}{\text{cross-sectional area}} + p_{\text{atm}}$$
$$= \frac{m_{\text{top}}g}{A} + p_{\text{atm}}$$
$$= \frac{\rho_f A h_1 g}{A} + p_{\text{atm}}$$
$$= \rho_f h_1 g + p_{\text{atm}}$$

Similarly, the pressure on the bottom surface is given by

$$p_{\text{bottom}} = \rho_f h_2 g + p_{\text{atm}}$$

Hence, the **upthrust** (resultant upward force) on the cylinder due to pressure difference between the top and bottom surfaces is

$$U = F_2 - F_1$$

= $\rho_f g (h_2 - h_1) A$
= $\rho_f g h A$
= $\rho_f g V_{\text{fluid displaced}}$
 $\therefore U = m_f g$

This gives us Archimedes's principle.

Definition 4.7: Principle of Floatation

The **principle of floatation** states that when an object is **floating in equilibrium** in a fluid, the **weight** of the object is equal to the weight of **fluid displaced** by the object.

 $W_{\text{object}} = W_{\text{fluid displaced}}$

An object floats because the **upthrust** acting on it is equal in magnitude and opposite in direction to the weight of the object. The object sinks when the upthrust acting on it is less than its weight.

A ship made of steel can float because its internal hollow volume displaces a large amount of water, producing sufficient upthrust to keep the ship floating.

4.6 Static Equilibrium

Definition 4.8: Equilibrium

When a body is in **equilibrium**, there is **no resultant force** acting on the body in any direction and no resultant moment acting on the body about any point.

Paraphrasing, the conditions for any body in equilibrium are that

- 1. the resultant force on it must be zero in any direction;
- 2. and the resultant torque on it must be zero about any axis of rotation.

4.6.1 Translational Equilibrium

When the resultant force on a body is zero in any direction, there is no acceleration of its centre of mass and the body is said to be in **translational equilibrium**.

If the forces can be resolved into components in two chosen perpendicular directions (such as the x and y axes), then

$$\sum F_x = 0$$
 and $\sum F_y = 0$

Similarly, since the resultant force acting on a body is zero, the **vector sum** of forces acting on the body must be zero in any direction as well. The vector diagram showing the addition of all forces acting on the body will be a closed polygon.

4.6.2 Rotational Equilibrium

When the resultant torque of a body is zero in any axis of rotation, there is no angular acceleration of the object and the body is said to be in **rotational equilibrium**. We introduce the notion of moments of a force, as well as the torque of a couple to formalise rotational equilibrium.

Definition 4.9: Moment of a Force

The **moment of a force** about a point is the product of the magnitude of the force and the perpendicular distance of the force from that point.

For a force $\vec{\mathbf{F}}$ acting on a body a perpendicular distance r_{\perp} away from the pivot, the magnitude of the moment τ is given by

$$\vec{\tau} = \vec{\mathbf{F}} \times \vec{\mathbf{r}} = Fr_{\perp}$$

Definition 4.10: Couple

A couple consists of a pair of forces of equual magnitude but acting in opposite directions whose lines of action are parallel but separate.

Definition 4.11: Torque of a Couple

The **torque of a couple** is the **product** of one of the forces and the perpendicular distance between the forces.

Considering the diagram below,

The magnitude of the torque of the couple, τ , is given by

$$\tau = \frac{1}{2}Fx + \frac{1}{2}Fx = Fx$$



Definition 4.12: Principle of Moments

The **principle of moments** states that when a system is in equilibrium, the sum of clockwise moments about any axis must be equal to the sum of anticlockwise moments about the same axis.

When the resultant torque of a body is zero about any axis of rotation, it further implies that the **sum of moments of all forces** acting on the body would be zero about any axis.

Hence, the principle of moments may be used to deal with bodies in rotational equilibrium.

For systems in equilibrium, the lines of action of the non-parallel forces **pass through a common point**.

5 Work, Energy & Power

5.1 Work

Definition 5.1: Work

Work, W, on an object by a constant force $\vec{\mathbf{F}}$ is the product of the force and displacement $\vec{\mathbf{s}}$ in the direction of the force.

$$W = \vec{\mathbf{F}} \cdot \vec{\mathbf{s}} = (F \cos \theta)s$$

where F is the magnitude of force, s is the magnitude of displacement, and θ is the angle between the force and the displacement vectors

Work is a *scalar quantity* with S.I. unit joule (J), representing the transfer of energy to a system.

For several forces acting on an object, the **net work done** is the sum of the work done by each force separately, or the dot product between the net force and the displacement.

$$\sum W = W_1 + W_2 + \dots + W_n$$
$$= \sum \vec{\mathbf{F}} \cdot \vec{\mathbf{s}} = \left(\sum F \cos \theta\right) s$$

5.1.1 Work Done by Variable Forces

For a body displaced by a variable force, the net work done is the **integral of the force** with respect to displacement \vec{s} .

$$\sum W = \int_{\vec{\mathbf{s}}_i}^{\vec{\mathbf{s}}_f} \sum \vec{\mathbf{F}} \, d\vec{\mathbf{s}}$$

In other words, the total work done on the body is equal to the **area under the force-displacement** graph.

5.2 Energy

Definition 5.2: Energy

Energy is the capacity to do work.

Energy is a *scalar quantity* with S.I. unit joule (J).

Definition 5.3: Principle of Conservation of Energy

The **principle of the conservation of energy** states that energy can neither be destroyed nor created. It can be transformed from one form to another and transferred from one body to another.

5.2.1 Kinetic Energy

Definition 5.4: Kinetic Energy

Kinetic energy is the energy that a body possesses solely due to its motion.

$$K = \frac{1}{2}mv^2$$

where K is the kinetic energy of a body of mass m moving with speed v.

Definition 5.5: Work-Energy Theorem

The **work-energy theorem** states that the work done by a resultant external force on a body is equal to the change in the kinetic energy of the body.

Proof. Consider an object of mass m moving through a displacement to the right under a net force $\sum \vec{\mathbf{F}}$, also directed to the right.

The net work done is

$$\sum W = \int_{x_i}^{x_f} \sum F \, dx$$

Using Newton's 2nd law, we substitute for the magnitude of the net force $\sum F = ma$, where m is constant,

$$\sum W = \int_{x_i}^{x_f} ma \, dx = \int_{x_i}^{x_f} m \frac{dv}{dt} \, dx = \int_{x_i}^{x_f} m \frac{dx}{dt} \, dv = \int_{v_i}^{v_f} mv \, dv$$
$$= \frac{1}{2} mv_f^2 - \frac{1}{2} mv_i^2$$

The common quantity $\frac{1}{2}mv^2$ is the kinetic energy, K. As such, we can rewrite the equation as

$$\sum W = K_f - K_i = \Delta K$$

Hence, the net work done is equal to the change in kinetic energy, provided that the system *only* undergoes translational motion, where speed is the only change. \Box

5.2.2 Potential Energy

Definition 5.6: Potential Energy

Potential energy is the ability to do work as a result of the position, shape, or state of an object.

For a conservative force F, it is related to the potential energy U such that

$$F = -\frac{dU}{dx}$$

The gradient of the potential energy-displacement graph gives the magnitude of the conservative force. In addition, the force points in the direction of **decreasing** potential energy.

One of the most pertinent forms of potential energy is **gravitational potential energy**, further formalised in Chapter 7. To simplify, on Earth's surface, gravitational potential energy of an object

is defined as

$$U_G = mgh$$

Consider an object at a certain height h_1 from the ground raised by a **constant force** F equal and opposite to the weight of the object. The object moves at a constant speed to a height h_2 , such that no work is used to increase its kinetic energy.

The weight mg is equal to the force F. The work done by the force F is thus

$$W = F \cdot s$$

= $mg(h_2 - h_1)$
= $mgh_2 - mgh_1$
= $(U_G)_f - (U_G)_i = \Delta U_G$

Thus, the work done by a force in raising an object through a vertical height h at a constant speed results in a **change** of the gravitational potential energy of the object.

5.3 Conservation of Mechanical Energy

Definition 5.7: Mechanical Energy

Mechanical energy of a system is the sum of the kinetic energy and potential energy in the system.

Definition 5.8: Principle of Conservation of Mechanical Energy

The **principle of conservation of mechanical energy** states that in the absence of any net external force, the total mechanical energy of the system is conserved.

$$\Delta K + \Delta U = 0$$

This principle illustrates that while the kinetic and potential energies of a system may be converted or transformed into one another, the **sum of the energies is always conserved**.

However, most moving bodies experience dissipative forces. In these situations, the total mechanical energy is **not conserved**. The work done by dissipative forces is equal to the loss in mechanical energy, that is,

$$K_i + P_i + W_d = K_f + P_f$$

The work done by the dissipative forces W_d is negative, as the forces always act in opposite direction to the displacement.

5.4 Power

Definition 5.9: Power

Power is defined as work done per unit time.

Power is a scalar quantity with S.I. unit watt. For a constant force $\vec{\mathbf{F}}$ acting on an object moving at a velocity $\vec{\mathbf{v}}$, the instantaneous power, P, is defined as

$$P = \frac{dW}{dt} = \frac{d(\vec{\mathbf{F}} \cdot \vec{\mathbf{s}})}{dt} = \vec{\mathbf{F}} \cdot \left(\frac{d\vec{\mathbf{s}}}{dt}\right) = \vec{\mathbf{F}} \cdot \vec{\mathbf{v}}$$

The average power $\langle P \rangle$ is given by

$$\langle P \rangle = \frac{W}{t} = \frac{\vec{\mathbf{F}} \cdot \vec{\mathbf{s}}}{t}$$

5.4.1 Efficiency

Due to inevitable work done by dissipative forces, the energy conversion can never be 100%. The useful energy output will almost always certainly be less than the energy input. The efficiency of a machine in its conversion of energy from one form to another is defined as

efficiency =
$$\frac{\text{useful energy output}}{\text{total energy input}} \times 100\%$$

6 Motion in a Circle

6.1 Radians

Consider an object moving in a circular arc. Let the radius of this circular path be r and the ball's travelled arc length be s with corresponding angular displacement θ .

The angle θ (in radians) is the ratio of the distance s along the circular arc subtended by θ divided by the radius r.

$$\theta = \frac{s}{r} \implies s = r\theta$$

In other words, a **radian** is the angle subtended at the centre of a circle by an arc of a length equal to the radius. If s = r, then θ is one radian. One radian is equal to 180° .

6.2 Angular Velocity

Definition 6.1: Angular Velocity

Angular velocity, denoted by $\vec{\omega}$, is the rate of change of angular displacement.

$$\vec{\boldsymbol{\omega}} = rac{d\vec{\boldsymbol{ heta}}}{dt}$$

When the angular velocity is constant, the body is said to be undergoing **uniform circular motion**.

$$\omega = \frac{\text{angular displacement}}{\text{time taken}} = \frac{\theta}{t}$$

If a body undergoing uniform circular motion takes T seconds to complete a full revolution,

$$\omega = \frac{\theta}{t} = \frac{2\pi}{T} = 2\pi f$$

where f represents the frequency of the circular motion.

6.2.1 Relation to Linear Speed

From $s = r\theta$, the linear speed of an object can be determined by considering the displacement derivative.

$$\frac{ds}{dt} = \frac{d(r\theta)}{dt} = r\frac{d\theta}{dt} + \theta\frac{dr}{dt}$$

If r is a constant, then

$$\frac{ds}{dt} = r \frac{d\theta}{dt}$$

Converting these derivatives to their representative quantities, we obtain an equation relating linear speed and angular velocity. This relationship is only valid when ω is measured in radians per second.

 $v=r\omega$

The direction of the linear velocity is tangential to the circular path. For an object rotating about an axis, every point on the object has the same angular velocity. The tangential speed of any point is proportional to its distance from the axis of rotation.

6.3 Centripetal Acceleration

Definition 6.2: Centripetal Acceleration

For a body in uniform circular motion, its acceleration is termed **centripetal acceleration** and is always perpendicular to the velocity of the object and points towards the centre of a circle.

$$a_c = \frac{v^2}{r} = v\omega = r\omega^2$$

Consider a body moving in a circular path of radius r with constant angular velocity ω . As it moves within an infinitesimally brief time interval dt, the magnitude of its linear velocity does not change, and the body moves an infinitesimal distance of arc length $r d\theta$.

Hence, the instantaneous *centripetal acceleration* of the body during this time interval is the derivative of linear velocity with respect to time, given by

$$a_{c} = \frac{dv}{dt} = \frac{d(r\omega)}{dt} = \omega \frac{dr}{dt} + r \frac{d\omega}{dt}$$
$$= v\omega = r\omega^{2} = \frac{v^{2}}{r} \quad \left(\because \frac{d\omega}{dt} = 0\right)$$

Using trigonometric principles, it is possible to show that the direction of centripetal acceleration of the body undergoing uniform circular motion is towards the centre of the circular path. Centripetal acceleration is always perpendicular to the tangential velocity of the body.

6.4 Centripetal Force

Applying Newton's 2nd law to a body of mass m, the centripetal force that must act to produce the uniform circular motion is

$$F = mr\omega^2 = m\frac{v^2}{r} = mv\omega$$

For uniform circular motion, the centripetal force is constant in magnitude and changing in direction.

As the centripetal force acts perpendicularly to the motion, it only changes the direction of velocity, but not the speed of the body. Moreover, due to its direction, *centripetal force does no work*.

If the centripetal force producing the centripetal acceleration vanishes, the object does not continue to move in its circular path; instead, it will move along a tangential path.

To solve a problem involving circular motion,

- 1. Draw a free-body diagram for the problem.
- 2. Identify the center of the circular motion.
- 3. Choose a suitable coordinate system.
- 4. Resolve the forces, if necessary.

5. Apply Newton's Second Law to solve the problem, while ensuring that r is the radius of the circular path.

6.4.1 Don't Draw the Centripetal Force

Consider an object moving in a uniform circular motion at constant angular velocity ω along a curved path from A to B.

Without external forces, Newton's 1st law tells us it would move in a straight line at constant speed. Since it follows a curve, an external force must therefore pull it towards the circle's center (which is, in fact, the centripetal force acting perpendicular of the object's motion to keep its speed constant).

According to Newton's 2nd law, this inward centripetal acceleration results from this force. However, it is important to note that the centripetal force *is not an extra force*; it represents the *net effect* of forces like tension and friction, and should not be drawn separately on free-body diagrams.

6.5 Turning Motion of Vehicles

Consider the following problem.

Example 6.1

A car of mass 750kg is taking a corner with a flat horizontal surface and a radius of 10m. If the lateral friction forces cannot exceed 1/10 of the weight of the vehicle, what is the maximum speed at which it can take the bend?

To begin, the frictional force by the road on the types is what provides the centripetal force.

$$f = m \frac{v^2}{r}$$

For maximum speed,

$$f_{\max} = m \frac{(v_{\max})^2}{r}$$
$$\implies \frac{mg}{10} = m \frac{(v_{\max})^2}{10}$$
$$\implies v_{\max} = \sqrt{g} = 3.1 m/s$$

 \therefore the maximum speed at which the car can take the bend is 3.1m/s or 11km/h.

Consider the forces acting on a racing car on mass m travelling around a circular bend along a flat horizontal track.

Neglecting air resistance, each tyre experiences its own normal reaction and frictional force, but the forces acting on the front and rear tyres are combined so that there are simply two normal reactions, N_1 and N_2 , and two frictional forces, f_1 and f_2 .

Resolving forces horizontally,

$$f_1 + f_2 = ma$$
Resolving forces vertically,

$$N_1 + N_2 = W$$

6.5.1 Banking Angle

As the types of the car can only provide a **maximum** friction, a car travelling too fast may not get around the bend. To reduce the possibility of skidding, the road can be **sloped** (or **banked**) so that the normal contact force of the road acting on the car provides a component directed to the centre of the circular path.

For a particular speed, this force will produce the exact centripetal force required. Otherwise, some lateral frictional force is needed.

Consider a car of mass m travelling on a slope of an angle θ between the road surface and the horizontal. Here, the horizontal component of the normal contact force N between the car and the road provides the centripetal force required to keep the car moving around the bend.



Resolving forces horizontally,

$$N_x = ma_c \implies N\sin\theta = m\frac{v^2}{r}$$

Resolving forces vertically,

$$N_y = W \implies N \cos \theta = mg$$

Dividing the first equation by the second,

$$\frac{N\sin\theta}{N\cos\theta} = m\frac{v^2}{r}\nabla\cdot mg \implies \tan\theta = \frac{v^2}{gr}$$

Hence, the optimal angle for the slope to be banked is given by

$$\theta = \arctan \frac{v^2}{gr}$$

6.6 Vertical Circular Motion

In vertical circular motion, the velocity of an object moving in a circular path differs as it travels between the bottom and the top of the loop.

Consider a body of mass m moving in a vertical circle of radius r on the end of a string.



At L and R, tension of the string provides the centripetal force.

At T and B, weight and normal contact force provide the centripetal force.

The speed changes as the mass moves upwards, as the **kinetic energy** increases as the expense of gravitational potential energy.

$$\Delta E_k = \Delta E_p$$

$$\frac{1}{2}mv_B^2 - \frac{1}{2}mv_T^2 = mg(2r)$$

$$v_B^2 - v_T^2 = 4gr$$

At T,

$$F_c = N + W = mg + m\frac{v^2}{r}$$

At B,

$$F_c = N - W = mg - m\frac{v^2}{r}$$

7 Gravitational Fields

There he sat at rest, in the intellectual center: as the great solar orb shining with its own light, & diffusing his beamy influence, thro' the whole system of arts, & sciences. To him gravitated all the lesser lights, both regular planets, & extravagant comets of erudition, both at home, & abroad.

- William Stukely, Memoirs of Sir Isaac Newton

7.1 Newton's Law of Gravitation

Definition 7.1: Newton's Law of Gravitation

Newton's law of gravitation states that the gravitational attraction between two point masses m_1 and m_2 is directly proportional to the product of their masses and inversely proportional to the square of the separation r between their centres.

$$F = \frac{Gm_1m_2}{r^2}$$

where $G = 6.67 \times 10^{-11}$ N m² kg⁻² is the gravitational constant of proportionality.

Note that **point masses** have non-zero mass but no volume. If two objects are placed sufficiently far apart (where their dimensions become negligible compared to separation), they can be considered point masses.

The gravitational forces between two masses are equal and opposite (recall Newton's Third Law), and always act along the line joining the two point masses.

To show its **attractive** nature, it is typically written as

$$ec{\mathbf{F}} = -rac{Gm_1m_2}{r^2}\mathbf{\hat{r}}$$

The negative sign is ignored when only the magnitude of the force is required.

7.2 Gravitational Field

Every object with mass sets up a gravitational field in its surrounding space.

When two objects enter each other's gravitational fields, they will be attracted towards each other. When an object with mass is placed in a gravitational field, it will **experience a gravitational force** acting on it.

7.2.1 Field Direction

The direction of a field at a point is along a tangent to the field line at that point.

The density of the field lines at a point (number of lines per unit area) corresponds to the strength of the field at that point. A **denser arrangement** of field lines indicates **greater gravitational field strength**.



7.2.2 Gravitational Field Strength

Definition 7.2: Gravitational Field Strength

The gravitational field strength g at a point of distance r from point mass M is defined as the gravitational force per unit mass exerted on a small test mass placed at that point.

$$\vec{\mathbf{g}} = -\frac{GM}{r^2}\hat{\mathbf{r}}$$

The gravitational field strength is a **vector** quantity with S.I. unit Nkg^{-1} .

Consider two point masses M and m separated by a distance r.



From Newton's law of gravitation, the magnitude of the attractive gravitational force F acting on m due to M is

$$F = \frac{GMm}{r^2}$$

Since gravitational field strength is force per unit mass, the magnitude of g at m's position is equal to

$$g = \frac{F}{m}$$

From these two equations,

$$g = \frac{GMm}{r^2} \Big/ m = \frac{GM}{r^2}$$

which is an expression for the **magnitude** of the gravitational field strength g at a point a distance r measured from a point mass M (it is M who **creates** the gravitational field).

A negative sign is used in the vector to show that the field strength points towards decreasing — $\hat{\mathbf{r}}$ is a unit vector in the **outward radial direction**.

At this junction, it is important to investigate the **constancy of field strength**, particularly for an affected point mass some minor distance away. The gravitational field strength g near the surface of the Earth is approximately constant at 9.81N kg⁻¹, which is also known as the acceleration of free fall with the value of 9.81m s⁻².

The approximate constancy should be appreciated by considering the value of g at height h above the surface, where h is small compared to the radius R of the Earth of mass M.

$$g = \frac{GM}{(h+R)^2} \approx \frac{GM}{R^2}$$
 for $h \ll R$

This is illustrated through the example below.

Example 7.1

Calculate the gravitational field strength at a height of 1km above the Earth's surface. The radius of the Earth is 6400km.

At the surface, using $g = \frac{GM}{r^2}$,

$$9.81 = \frac{GM_E}{R_E^2} = \frac{GM_E}{(6400 \times 10^3)^2}$$

At a height of 1km, r = 6401km,

$$g_1 = \frac{GM_E}{r^2} = \frac{GM_E}{(6401 \times 10^3)^2} = 9.81 \times \frac{(6400 \times 10^3)^2}{(6401 \times 10^3)^2} = 9.81$$

7.3 Gravitational Potential Energy

Near the Earth's surface, gravitational potential energy takes on an elementary expression: it is simply denoted by U = mgh. However, when dealing with non-negligible distances away from Earth's surface, we must confront a more unwieldy formulation.

Definition 7.3: Gravitational Potential Energy

The gravitational potential energy of a mass at a point is defined as the work done on the mass in moving it from infinity to that point.

$$U = -\frac{GMm}{r}$$

Here, the work is done by an external force acting in the **opposite direction** to the gravitational attraction.

Alternatively, the gravitational potential energy of a mass at a point can also be understood as the **work done against gravity** in bringing the mass from infinity to that point.

To illustrate the meaning of the gravitational potential energy U, considering moving a mass m from infinity to a point A, at distance r from the centre of a mass M, at constant speed.

 $\vec{\mathbf{F}}_g$ represents gravitational force acting on m by M, while $\vec{\mathbf{F}}_{ext}$ represents the force acting on m by an external agent such that $|\vec{\mathbf{F}}_{ext}| = |\vec{\mathbf{F}}_g|$.



Mathematically, in combination with Newton's 3rd law, the definition can be written as

$$U = \int_{\infty}^{r} \vec{\mathbf{F}}_{ext} dr$$
$$= \int_{\infty}^{r} -\vec{\mathbf{F}}_{g} dr$$
$$= \int_{\infty}^{r} \left(\frac{GMm}{r^{2}}\right) dr$$
$$= \left[-\frac{GMm}{r}\right]_{\infty}^{r} = -\frac{GMm}{r}$$

As iterated in Chapter 4, the gravitational force is the derivative of U with respect to r.

$$F = -\frac{dU}{dr}$$

7.3.1 Gravitational Potential

Definition 7.4: Gravitational Potential

The **gravitational potential** at a point is defined as the work done per unit mass (by an external force) in bringing a small test mass from infinity to that point.

$$\phi = \frac{U}{m} = -\frac{GM}{r}$$

```
It is a scalar quantity with S.I. unit Jkg^{-1}.
```

The gravitational potential energy of a mass depends on both the value of the mass as well as the position of the mass.

The gravitational potential is an energy-related quantity solely dependent on the position in a gravitational field. Moreover, the gravitational field strength g can be said to be the negative gradient of the gravitational potential ϕ with respect to r.

$$g=-\frac{d\phi}{dr}$$

7.4 Energy Considerations

7.4.1 Total Energy

With the formal definition of gravitational potential energy, we are able to analyse the energy for a body of mass m orbiting around a larger body of mass M.

Since gravitational force provides centripetal force,

$$\sum F = ma \implies \frac{GMm}{r^2} = \frac{mv^2}{r}$$
$$\implies \frac{1}{2}mv^2 = \frac{GMm}{2r}$$

Hence, for gravitation,

$$E = K + U = \frac{GMm}{2r} + \left(-\frac{GMm}{r}\right) = -\frac{GMm}{2r}$$

The above holds true for circular orbits. For elliptical orbits, simply take r to be the semi-major axis length.

7.4.2 Escape Velocity

As an object travels indefinitely away from a body, $r \to \infty$, hence $K \to 0$, $U \to 0$, and $E \to 0$. As such, at infinity, we take the kinetic energy and gravitational potential energy to be zero.

Since the object-Earth system is isolated, calculating the minimum escape velocity v,

$$\Delta U = -\Delta K \implies 0 - \left(-\frac{GMm}{r}\right) = -\left(0 - \frac{1}{2}mv^2\right)$$
$$\implies \frac{GMm}{r} = \frac{1}{2}mv^2$$
$$\implies v = \sqrt{\frac{2GM}{r}}$$

If the initial velocity is greater than the minimum escape velocity required, the object will have some residual kinetic energy as $r \to \infty$.

7.5 Kepler's Third Law

Take the situation of the circular motion of our Moon (of mass m) assumed to be circulating about our Earth (of mass M) in a circular orbit of radius r.

This simplifies the case to a **gravitational one-body problem**, where one object orbits about a point under the influence of gravity.

The gravitational force acting on the Moon by the Earth provides the centripetal force, giving

acceleration $a_c = r\omega^2$.

$$\sum F = ma \implies \frac{GMm}{r^2} = mr\omega^2$$
$$\implies \omega^2 = \frac{GM}{r^3}$$
$$\implies \left(\frac{2\pi}{T}\right)^2 = \frac{GM}{r^3}$$
$$\implies r^3 = \frac{GM}{4\pi^2}T^2$$
$$\implies \left[r^3 \propto T^2\right]$$

This is known as **Kepler's Third Law**, which states that the square of a body's orbital period is proportional to the cube of the length of the semi-major axis of its orbit.

7.6 Geostationary Orbits

Geostationary orbits are circular orbits made by satellites about the Earth's axis such that these satellites would **appear stationary when observed from a point on the surface of the Earth**. This allows for the satellite to provide permanent coverage of a given wide area.

- 1. They must move **west to east** (moves in the same sense of self-rotation of the Earth about its own axis).
- 2. The satellite's **orbital period must be equal to 24 hours** (so that it is the same as Earth's rotational period about its own axis).
- 3. The geostationary orbit is an equatorial **equatorial orbit** (an orbit in the plane of the equator) for the satellite to remain in a fixed relative position above the Earth's surface, its axis of rotation has to coincide with Earth's axis of rotation.

Part III Thermal Physics

8 Temperature and Ideal Gases

Every mathematician knows it is impossible to understand an elementary course in thermodynamics.

— Vladimir Igorevich Arnold

8.1 Zeroth Law of Thermodynamics

Temperature is a measure of the degree of hotness of an object. Thermal energy moves from objects of higher temperatures to objects of lower temperatures. Note that temperature does not measure an object's thermal energy.

Heat is **energy** that flows from a higher-temperature object to a lower-temperature object due to differences in temperature.

Definition 8.1: Thermal Equilibrium

When two objects in thermal contact has no *net heat transfer* between them, they are said to be in **thermal equilibrium** and are at the same temperature.

Definition 8.2: Zeroth Law of Thermodynamics

The **zeroth law of thermodynamics** states that if two objects A and B are separately in thermal equilibrium with object C, then objects A and B must be in thermal equilibrium with each other.

This forms the basis for the measurement of temperature — the object C named above can function as a measuring device known as a *thermometer*.

8.2 Temperature Scales

Thermometers measure temperature based on a physical property that changes with temperature.

8.2.1 Empirical Temperature Scale

An **empirical temperature scale** is a scale of temperature that is based on the variation with temperature of a property of a substance, *assuming* that the property varies linearly with temperature.

To set up an empirical temperature scale,

- 1. Choose an appropriate thermometric property, which can be one of the following:
 - volume of fixed mass of liquid
 - resistance of a metal
 - pressure of a fixed mass of gas at constant temperature
 - electromotive force produced between junctions of dissimilar metals at different temperatures

- 2. Select two fixed temperature points; an upper point and a lower point to calibrate the thermometer.
- 3. Calibrate the thermometer by placing the thermometer at the two points, and record the thermometric quantity, letting the value at the lower point be X_0 and that at the upper point be X_{100} .

With these two values, and holding the assumption that there exists a linear relationship between these two points, the temperature θ of any subsequent medium can be calculated as shown.

$$\theta = \frac{X_{\theta} - X_0}{X_{100} - X_0} \times 100$$

8.2.2 Absolute Temperature Scale

The **absolute temperature scale** (also thermodynamic temperature scale) does not depend on the thermometric property of any particular substance, and has absolute zero and the triple point of water as fixed points.

- Absolute zero, defined as -273.15° C or 0K, is the temperature at which all substances have minimum internal energy.
- The triple point of water is the particular temperature and pressure (273.16K, 4.58mmHg) at which the three states of water can co-exist in equilibrium.

In other words, the absolute temperature scale is not based on any thermometric property, but rather on the theoretical efficiency of a perfectly reversible heat engine.

8.3 Ideal Gas Law

Definition 8.3: Ideal Gas

An ideal gas is a hypothetical gas that obeys the equation of state

$$PV = nRT$$

perfectly at all pressures P, volumes V, amounts of substances n, and temperatures T.

For an ideal gas with volume V, pressure P, and temperature T, experiments have shown that

- by Charles' law, $V \propto T$ when P is constant;
- by Boyle's law, $P \propto 1/V$, when T is constant;
- by Gay-Lussac's law, $P \propto T$, when V is constant.

These laws give the **ideal gas law** where n is the number of **moles** of gas, and R = 8.31 J K/mol is the **universal gas constant**.

$$PV = nRT$$

This can be rewritten as, where N is the number of **molecules** of gas, and $k = R/N_A = 1.38 \times 10^{-23} \text{ J/K}$ is **Boltzmann's constant**.

$$PV = NkT$$

Avogadro's Number

One mole is the amount of substance containing 6.02×10^{23} particles.

The mathematical relationship between n and N is

$$N = nN_A$$

where $N_A = 6.02 \times 10^{23}$ is **Avogadro's number**.

8.4 Kinetic Theory of Gases

In the kinetic theory of gases, the assumptions imposed on ideal gases are:

- all gases consist of a very large number of atoms or molecules;
- the atoms or molecules behave as if they are hard, perfectly elastic, identical spheres;
- the molecules are in constant, random motion, and obey Newton's laws of motion;
- there are no forces of attraction or repulsion between atoms or molecules unless they are in collision with each other or with the walls of the container (*therefore potential energy is zero*);
- total volume of atoms or molecules is negligible compared with the volume of the container;
- time of collisions is negligible compared with time between collisions.

8.4.1 Molecular Model

Consider a cubical box of sides l, containing N molecules of a gas, where the mass of each molecule is m.

By considering the *elastic collision of one molecule* (with x-velocity c_x) with a wall, the change in momentum of the molecule due to the collision is

$$\Delta p_i = -2mc_{xi} \implies \Delta p_{\text{wall}} = 2mc_{xi}$$

The next time the same molecule collides with the same wall, the molecule would have travelled a total distance of 2l in the x direction. Hence, the time Δt between collisions is

$$\Delta t = \frac{2l}{c_{xi}}$$

Therefore, the rate of change of momentum for the wall due to one molecule is

$$F_{i} = \frac{\Delta p_{\text{wall}}}{\Delta t} = (2mc_{xi}) \left(\frac{c_{xi}}{2l}\right) = \frac{mc_{xi}^{2}}{l}$$

From Newton's second law,

$$F_{\text{wall}} = \sum_{i=1}^{N} \frac{m c_{xi}^{2}}{l} = \frac{m}{l} \sum_{i=1}^{N} c_{xi}^{2}$$

From the definition of mean square speed,

$$\langle c_x^2 \rangle = \frac{c_{x1}^2 + c_{x2}^2 + \dots + c_{xN}^2}{N} \implies F_{\text{wall}} = \frac{Nm}{l} \langle c_x^2 \rangle$$
$$\implies P_{\text{wall}} = \frac{F_{\text{wall}}}{l^2} = \frac{Nm}{V} \langle c_x^2 \rangle$$

Applying Pythagoras' theorem to the 3-dimensional velocity vector for any molecule leads to

$$c^{2} = c_{x}^{2} + c_{y}^{2} + c_{z}^{2}$$
$$\langle c^{2} \rangle = \langle c_{x}^{2} \rangle + \langle c_{y}^{2} \rangle + \langle c_{z}^{2} \rangle$$

However, we assume that the motion of particles is isotropic in the kinetic theory, such that $\langle c_x^2 \rangle = \langle c_y^2 \rangle = \langle c_z^2 \rangle$. Therefore, $\langle c_x^2 \rangle = \langle c^2 \rangle/3$.

Using this expression, we can find the total force and pressure exerted on the wall.

$$F = \frac{1}{3} \frac{Nm}{l} \langle c^2 \rangle \implies PV = \frac{1}{3} Nm \langle c^2 \rangle$$

8.4.2 Average Molecular Kinetic Energy

Notice that we obtain two forms of the expression PV. This allows us to relate average **translational molecular kinetic energy** to temperature.

$$PV = \frac{Nm}{3} \langle c^2 \rangle = NkT \implies T = \frac{2}{3k} \left(\frac{1}{2} m \langle c^2 \rangle \right)$$
$$\implies \boxed{\frac{1}{2} m \langle c^2 \rangle = \frac{3}{2} kT}$$

8.4.3 Representations of Ideal Gas Law

The kinetic theory of gases helps to spawn many other equivalent representations of the ideal gas law.

$$PV = nRT = NkT = \frac{1}{3}Nm\langle c^2 \rangle$$

To summarise, for a pressure P, volume V, amount of moles of gas n, amount of molecules of gas N, mass per molecule m, total mass of gas M, and molar mass of gas M_m , we have the three following equations.

Given density,

$$PV = \frac{1}{3}Nm\langle c^2 \rangle \implies PV = \frac{1}{3}M\langle c^2 \rangle \quad (\because M = Nm)$$
$$\implies c_{\rm rms} = \sqrt{\langle c^2 \rangle} = \sqrt{\frac{3PV}{M}} = \boxed{\sqrt{\frac{3P}{\rho}}}$$

Given molar mass,

$$PV = nRT \implies \frac{1}{3}M\langle c^2 \rangle = \frac{M}{M_m}RT$$
$$\implies \langle c^2 \rangle = \frac{3RT}{M_m}$$
$$\implies c_{\rm rms} = \boxed{\sqrt{\frac{3RT}{M_m}}}$$

Given molecular mass,

$$PV = NkT \implies \frac{1}{3}Nm\langle c^2 \rangle = NkT$$
$$\implies c_{\rm rms} = \boxed{\sqrt{\frac{3kT}{m}}}$$

9 First Law of Thermodynamics

9.1 Internal Energy

For a system with N molecules, the **state** of the system is defined by its pressure P, volume V, and thermodynamic temperature T.

Definition 9.1: Internal Energy

The **internal energy of a system** is the **sum** of the **kinetic energy** due to the random motion of the molecules, and the **potential energy** due to the intermolecular forces of attraction.

 $U_i = \sum K + \sum U_p = \sum K$ (:: $U_p = 0$ for ideal gases)

For a stationary system, the internal kinetic energy of all the molecules is the sum of their **random kinetic energy**.

The internal potential energy of the molecules is due to the **work done to move them further apart against intermolecular attraction**. In ideal gases, we assume that there is no attraction between molecules, hence internal potential energy is considered to be **zero**.

9.1.1 Increase in Thermodynamic Temperature

As mentioned, for an **ideal gas**, its molecules have **no intermolecular attraction** (thus *no* random potential energy), meaning that all internal energy is due to its random kinetic energy. Recall that

$$\langle K\rangle = \frac{1}{2}m\langle c^2\rangle = \frac{3}{2}kT$$

The internal energy U of an ideal gas with N molecules is thus

$$U = \sum K = N \langle K \rangle = \frac{3}{2} N k T \implies U \propto T$$

The internal energy of a fixed mass of ideal gas is **directly proportional** to its thermodynamic temperature. A rise in temperature of an ideal gas indicates **a rise in the average random kinetic energy** of the molecules.

One might also note that U is simply a function of state, as described later on in the isotherm, a state can be described by a unique pair of coordinates (P_i, V_i) . As such, each $U = \frac{3}{2}PV$ can be tied to a distinct point on the P-V graph (a.k.a. a state).

9.2 Heat Capacity

The heat capacity C of an object is the thermal energy Q per unit temperature change ΔT

$$Q = C\Delta T$$

Note that C = mc, where c is the specific heat capacity as defined below. The unit of C is J K⁻¹.

Symbol	Meaning	Formula	
ΔU	Positive \rightarrow increase in internal energy	For an ideal gas, $\Delta U = \frac{3}{2}Nk\Delta T$	
	Negative \rightarrow decrease in internal energy		
Q	Positive \rightarrow heat supplied to the system	$Q = mc\Delta T$ or $Q = mI$	
	Negative \rightarrow heat removed from the system	$Q = mc\Delta I$ of $Q = mL$	
W	Positive \rightarrow volume of system decreases	$W = -\int_{V_1}^{V_2} p dV$	
	Negative \rightarrow volume of system increases		

9.2.1 Specific Heat Capacity

Definition 9.2: Specific Heat Capacity

The specific heat capacity c of a subsatuce is defined as the thermal energy per unit mass per unit temperature change.

If the thermal energy Q supplied to a mass m of the substance changes its temperature by ΔT , then

$$c = \frac{Q}{m\Delta T} \implies Q = mc\Delta T$$

9.2.2 Specific Latent Heat

Definition 9.3: Specific Latent Heat

The **specific latent heat** of a substance is defined as the thermal energy per unit mass required to change its state at constant temperature.

From solid to liquid, it is latent heat of fusion, and latent heat of solidification for the reverse. They occur at the substance's melting point, with constant pressure.

From liquid to gas, it is latent heat of vaporisation, and latent heat of condensation for the reverse. They occur at the substance's boiling point, with constant pressure.

If the thermal energy Q supplied to a substance causes a change in state of a mass m of the substance, then the specific latent heat of the substance L is expressed as

$$L = \frac{Q}{M} \implies Q = mL$$

9.3 First Law of Thermodynamics

Definition 9.4: First Law of Thermodynamics

The first law of thermodynamics states that the increase in internal energy of a system is the sum of the heat supplied to the system and the work done on the system.



9.3.1 Isotherm

The state of a system can be represented by a point in the P/V graph.

Using the ideal gas equation PV = nRT, the temperature is of a specific value once there are specific values for P and V.

At constant temperature, the product PV is a constant, thus the P/V is a hyperbola called the **isotherm**.

From the above graph, since the larger the value of PV, the higher T is, hence $T_2 > T_1$.

9.3.2 Types of Processes

An adiabatic process is a (fast) process during which **no heat** is supplied to or removed from the system.

• $Q = 0 \implies \Delta U = W$

An isobaric process is a process that occurs at constant pressure.

- $W = -P\Delta V$
- Constant pressure means the environment is not changing final state is on a different isotherm, with changes in T and V.

An isovolumetric (or isochoric) process is a process that occurs at constant volume.

- $V_f = V_i \implies W = 0 \implies \Delta U = Q.$
- Usually means the system is confined within a rigid container, with zero work done by and on the system final state is on a different isotherm, with changes in T and P.

An isothermal process is a process that occurs at constant temperature.

•
$$\Delta U = 0 \implies Q = -W$$

- The P V graph is a hyperbolic curve called an **isotherm**; constant temperature \rightarrow constant total random kinetic energy \rightarrow **constant internal energy**.
- Both P and V change, but the product PV is constant.

For cyclic processes, the graph maps the transitions between the thermodynamic states of the gas. At the end of 1 cycle, the gas **returns to its original thermodynamic state**, thus the overall change in internal energy across the entire cyclic process $\Delta U = 0$.

Part IV Oscillations and Waves

10 Oscillations

Definition 10.1: Oscillation

An oscillation is a periodic to-and-fro motion of an object between two limits.

There are three types of oscillations: free oscillations, damped oscillations, and forced oscillations.

10.1 Free Oscillations

Definition 10.2: Free Oscillation

When an object undergoes **free oscillation**, it oscillates with **no energy gain or less**. The object oscillates with **constant amplitude**, as there are no external forces acting on it.

In the absence of any drag force, an oscillatory motion can be graphically represented by a **sinu-soidal curve**.

As such, we can mathematically describe its **displacement** (x) with respect to time (t) as the following general question, where we are usually concerned with the particular solutions in which $\phi = 0^{\circ}$ or $\phi = 90^{\circ}$.

$$x = x_o \sin(\omega t)$$
 or $x = x_o \cos(\omega t)$

For the sine curve equation, the object passes the equilibrium position at t = 0. For the cosine curve equation, the object is at the extreme position at t = 0.

The following physical quantities are used to characterise oscillatory motions.

Definition 10.3: Amplitude (Oscillations)

The **amplitude**, x_0 , is the **maximum displacement** of the oscillating object from the **equilibrium position**.

Definition 10.4: Displacement (Oscillations)

The **displacement**, x, is the distance of the oscillating object from its equilibrium position in a stated direction.

Definition 10.5: Period (Oscillations)

The **period**, T, is the time taken for one complete oscillation.

Definition 10.6: Frequency (Oscillations)

The **frequency**, f, the number of complete to-and-fro cycles per unit time made by the oscillating object.

 $f = \frac{1}{T}$

Definition 10.7: Angular Frequency

The **angular frequency**, ω , is the constant which characterises the particular simple harmonic oscillator and is related to its natural frequency.

$$\omega = 2\pi f = \frac{2\pi}{T}$$

10.1.1 Phase

Apart from the quantities mentioned above, there are two additional quantities of importance. The **phase** is an angle which gives a measure of the fraction of a cycle that has been completed by an oscillating particle or by a wave.

- The phase of the motion of a particle is the quantity $(\omega t + \phi)$.
 - At the stage when 1/4 cycle is completed, the phase is $\pi/2$ radians.
 - At the stage when 1/2 cycle is completed, the phase is π radians.
 - At the stage when 3/4 cycle is completed, the phase is $3\pi/2$ radians.
- A graph of $x = x_o \cos(\omega t + \phi)$ is the graph of $x_o \cos \omega t$ displaced to the left by a time interval $\frac{\phi}{\omega}$, with the plus sign indicating the motion leads by time $\frac{\phi}{\omega}$.
- A graph of $x = x_o \cos(\omega t \phi)$ is the graph of $x_o \cos \omega t$ displaced to the right by a time interval $\frac{\phi}{\omega}$, with the negative sign indicating the motion lags behind by time $\frac{\phi}{\omega}$.

The **phase difference** between two oscillations is a measure of how much one oscillation is out of step with another.

- If two oscillations are in step with one another, they are said to be **in phase** with one another (phase difference = 0)
- Two oscillations are said to be in anti-phase (phase difference = π) when the displacement of each oscillation is completely opposite to each other.

10.2 Simple Harmonic Motion

Definition 10.8: Simple Harmonic Motion

Simple harmonic motion is defined as the oscillatory motion of a particle whose acceleration is directly proportional to its displacement from a fixed point and this acceleration is always in opposite direction to its displacement.

$$a = -\omega^2 x$$

where x is the displacement from the equilibrium position, and ω^2 is the constant of proportionality.

The constant is a squared quantity to ensure it is always positive — as such, the acceleration a is always opposite to the direction of displacement x.

Note that the acceleration of a body undergoing simple harmonic motion is always directed towards the equilibrium position — the position at which **no net force** acts on the oscillating object.



To prove that $x = x_0 \sin \omega t$ is a particular solution to the defining equation $a = -\omega^2 x$,

$$v = \frac{dx}{dt} = \omega x_0 \cos \omega t$$
$$a = \frac{dv}{dt} = -\omega^2 (x_0 \sin \omega t) = -\omega^2 x$$

Re-examining, we can obtain the velocity-time relationship by

$$v = \frac{dx}{dt} = x_0 \omega \cos \omega t$$
$$\implies v = v_0 \cos \omega t$$

The velocity can also be more explicitly given by

$$v = \pm \omega \sqrt{(x_o^2 - x^2)}$$

Similarly, we can find the acceleration-time relationship.

$$a = \frac{dv}{dt} = -v_0 \omega \sin \omega t$$
$$\implies a = -a_0 \sin \omega t$$

10.2.1 Graphical Illustration

Below are the graphs to describe the equations for displacement, velocity, and acceleration during free oscillatory motion.

The graphs of x-v and v-a have a phase difference of $\frac{\pi}{2}$. In other words, the displacement-time graph and acceleration-time graph are **in anti-phase** with each other.

10.2.2 Energy Expressions

The principle of conservation of mechanical energy states that the total energy in an isolated system is constant.

For an oscillator in simple harmonic motion, its **total energy** is the sum of its **kinetic** and **potential** energy.

$$E_{\text{total}} = E_{\text{kinetic}} + E_{\text{potential}}$$

If $x = x_0 \sin \omega t$, then $v = \omega \sqrt{(x_o^2 - x^2)}$, thus allowing us to express E_k in terms of t,

$$E_k = \frac{1}{2}mv^2 = \frac{1}{2}m\omega^2(x_0^2 - x^2)$$
$$= \frac{1}{2}m\omega^2x_0^2\cos^2(\omega t)$$

The maximum kinetic energy of an oscillator in simple harmonic motion is given by

$$E_k = \frac{1}{2}m\omega^2 x_0^2$$

and occurs when the oscillator is at its equilibrium position.

When the kinetic energy of an oscillating object is at its maximum, its potential energy must be at its minimum, since the total energy is constant.

If we define the minimum E_p to be 0, then

$$E_T = E_k = E_p$$

Thus, in terms of t,

$$\frac{1}{2}m\omega^2 x_0^2 = \frac{1}{2}m\omega^2 x_0^2 \cos^2(\omega t) + E_p$$
$$E_p = \frac{1}{2}m\omega^2 x_0^2 \sin^2(\omega t)$$

or, in terms of x,

$$\frac{1}{2}m\omega^2 x_0{}^2 = \frac{1}{2}m\omega^2(x_0{}^2 - x^2) + E_p$$
$$E_p = \frac{1}{2}m\omega^2 x^2$$

10.2.3 Energy Changes during Oscillation

Consider one cycle of the motion of a simple pendulum in the absence of energy losses to the surroundings, where the pendulum moves $A \to B \to A \to C \to A$.

At extreme positions B and C, where the bob is at maximum displacement, it has **maximum potential energy** and **minimum kinetic energy**. At the equilibrium position A, where the bob has zero displacement, it has **minimum potential energy** and **maximum kinetic energy**. In between the equilibrium position and the extreme position, the bob has a combination of potential and kinetic energy.

Since simple harmonic motion is assumed to take place in a closed system, the **total energy** remains constant.



10.2.4 Vertical Spring-Mass System

A vertically-oscillating spring-mass system interchanges three types of energies — kinetic energy, gravitational potential energy, and elastic potential energy.



Assuming that the spring obeys Hooke's law, and that $y_0 \leq e$,

The total energy in the isolated system is the sum of all three energies. In equilibrium, the mass experiences gravitational weight mg and the restoring force of the spring kx. This means that kx = mg.

Position	KE	GPE	EPE
Highest point, $y = -y_0$	0	$2mgy_0$	$\frac{1}{2}k(e-y_0)^2$
Equilibrium position, $y = 0$	$\frac{1}{2}m\omega^2 y_0^2$	mgy_0	$\frac{1}{2}ke^2$
Lowest point, $y = +y_0$	0	0	$\frac{1}{2}k(e+y_0)^2$
General displacement y	$\frac{1}{2}m\omega^2(y_0^2 - y^2)$	$mg(y_0 - y)$	$\tfrac{1}{2}k(e+y)^2$

10.3 Damped Oscillations

Definition 10.9: Damping

Damping is a process where energy is taken from an oscillating system as a result of dissipative forces.

Definition 10.10: Damped Oscillation

Damped oscillation occurs when there is a continuous dissipation of energy to the surroundings such that the total energy in the system decreases with time, hence the amplitude of the motion progressively decreases with time.

There are three degrees of damping.

Light damping, where the object undergoes a number of complete oscillations with the amplitude of vibration decreasing exponentially with time. One example is a vertical simple spring-mass system in air or in a low-viscosity liquid.



Displacement-time graph of a lightly damped oscillator.

Critical damping, where no oscillations occur. The displacement is brought to zero in the *shortest possible time*. An example is a car with a suspension system which reduces discomfort on bumpy roads.

Heavy damping, where no oscillations occur about the equilibrium position when the damping force increases beyond the point of critical damping. The system *takes a longer time to return to the equilibrium position* compared to the critically damped system.



Displacement-time graph of a critically damped oscillator (red) and a heavily damped oscillator (black).

10.3.1 Car Suspension Systems

The degree of damping a mechanical system is important — a suspension system of a car should ensure that passengers are comfortable when moving on bumpy roads.

If the suspension is only **lightly damped**, passengers would be thrown up and down since the suspension system would take quite long to stop oscillating. This might also damage the car.

A good suspension system is one where shock absorbers on a car **critically damp** the suspension of the vehicle.

10.4 Forced Oscillations

Definition 10.11: Forced Oscillations

Forced oscillations are caused by the continual input of energy by external applied force to an oscillating system to compensate the loss due to damping in order to maintain the amplitude of the oscillation.

The system then oscillates at the frequency of the external periodic force.

10.4.1 Resonance

When the driving frequency f equals the natural frequency of a system f_0 , the amplitude of the oscillation will be a **maximum**. This is called **resonance**.

Definition 10.12: Resonance

Resonance occurs when the **resulting amplitude of the system becomes a maximum** when the driving frequency of the external driving force equals the natural frequency of the system.

Useful applications of include include radio and musical instruments, wheras undesirable effects of resonance include the shattering of glass (with the correct frequency and amplification) and resonance in rigid structures.

10.4.2 Frequency Response Graph

The graph below shows how the amplitude x_0 of a forced oscillation depends on the driving frequency f when the damping of the system is light, and when the damping of the system is heavy.



For a forced oscillation, when conditions are **steady**, one observes the following:

- the amplitude of a forced oscillation depends upon
 - the damping of the system; and
 - the relative values of the driving frequency f and the natural frequency f_0 of free oscillation (i.e. how far f is from f_0)
- the vibrations with largest amplitude (i.e. resonance) occur when f is equal to f_0

As damping increases,

- the response is **less sharp** (with a lower and flatter peak and smaller amplitudes at all frequencies), and
- the maximum amplitude is reached when the driving frequency is **slightly less than** the natural frequency

11 Wave Motion

11.1 Waves

11.1.1 Types of Waves

Definition 11.1: Progressive Wave

A **progressive wave** is a wave in which energy is carried from out point to another by means of vibrations or oscillations within the wave, without transporting matter.

Definition 11.2: Transverse Wave

A **transverse wave** is a wave with vibrations perpendicular to the direction of transfer of the wave's energy.

Definition 11.3: Longitudinal Wave

A **longitudinal wave** is a wave with vibrations parallel to the direction of transfer of the wave's energy.

Definition 11.4: Mechanical Wave

A mechanical wave is a wave that requires a medium for its transmission.

Definition 11.5: Electromagnetic Wave

A electromagnetic wave is a wave that consists of oscillating electromagnetic fields that are perpendicular to each other and to the direction of transfer of the wave's energy. They do not require a medium for transmission.

11.1.2 Electromagnetic Spectrum

Name	Wavelength	Uses
Radio waves	>10cm	Communications, radioastronomy
Microwaves	1mm to 10cm	Communications, cooking
Infrared	700nm to 1mm	Satellite surveying, TV controls
Visible light	400nm to 700nm	Sight, communication
Ultraviolet	1nm to 400 nm	Food sterilisation, atomic structures
X-rays	1pm to 1nm	Diagnosis, radiotherapy, astronomy
Gamma rays	1fm to 1pm	Diagnosis, radiotherapy

All electromagnetic waves travel in vacuum with the same speed of $c = 3.0 \times 10^8$ metres per second.

All electromagnetic waves transfer energy from one place to another and can be absorbed and emitted by matter.

11.1.3 Wave Characteristics

Definition 11.6: Displacement (Waves)

Displacement is the distance in a specific direction of a point on the wave from its equilibrium position.

Definition 11.7: Amplitude (Waves)

The **amplitude** is the maximum displacement of any point on the wave from its equilibrium position.

Definition 11.8: Period (Waves)

The **period** T is the time taken for one complete oscillation of a point in a wave.

Definition 11.9: Frequency (Waves)

The **frequency** f is the number of oscillations per unit time of a point on a wave.

$$f = \frac{1}{T}$$

Definition 11.10: Wavelength

The wavelength λ is the minimum distance between any two points of the wave with the same phase at the same instant.

Definition 11.11: Wave Speed

The wave speed v is the speed at which energy is transmitted by a wave.

$$v = \frac{\lambda}{T} = f\lambda$$

Definition 11.12: Wavefront

A wavefront is an imaginary line joining points which are in phase.

- Wavefronts are usually drawn one wavelength apart and represent wave crests.
- They are always perpendicular to the direction of wave propagation.
- All the points on a wavefront have the same distance from the source of the wave.

Definition 11.13: Ray

A **ray** is a line pointing in the direction of energy transfer. Rays are always perpendicular to wavefronts.

11.1.4 Graphical Representations

Displacement-Distance Graph

The displacement-distance graph shows how particle displacement varies with the distance from the source at any chronological instant. The **wavelength** can be deduced from the graph.



Displacement-Time Graph

The displacement-time graph shows how the displacement of a singualr wave particle varies with time. The **period** can be deduced from the graph.



11.1.5 Phase

Definition 11.14: phase

The **phase** ϕ is an angle which gives a measure of the **fraction of a cycle** that has been completed by an oscillating particle or wave.

One cycle corresponds to 2π radians.

The **phase difference** $\Delta \phi$ is a measure of how much one wave is out of step with another. Two particles are **in phase** if $\Delta \phi = 0$. Two particles are in **anti-phase** if they are out of phase by a half cycle, where $\Delta \phi = \pi$.

$$\Delta \phi = \frac{\Delta x}{\lambda} \times 2\pi = \frac{\Delta t}{T} \times 2\pi$$

11.2 Cathode Ray Oscilloscope

A **cathode ray oscilloscope** is a device used to study waveforms, measure voltage, and measure short time intervals.

This is usually employed in practicals.

11.2.1 Frequency Determination

In order to determine the *frquency* of a sound using a calibrated cathode ray oscilloscope, the following steps are taken.

- 1. A signal is fed through a microphone into a cathode-ray oscilloscope.
- 2. With the time-base of the oscilloscope turned on, the trace on the oscilloscope screen will be a display of the displacement against time.
- 3. The time-base of the oscilloscope is adjusted until a stationary trace is obtained.
- 4. The period T of the sound wave is given by the product of the length l of the one complete cycle, and the time-base setting b of the oscilloscope.

$$T = lb \implies f = \frac{1}{lb}$$

11.2.2 Wavelength Determination

In order to determine the *wavelength* of a sound using a calibrated cathode ray oscilloscope, the following steps are taken.

- 1. A loudspeaker delivers a sound through a signal generator; the incident wave is directed towards and reflected at the reflector plate.
- 2. Superposition of the incident wave and the reflected wave (which have equal properties, except opposing directions of travel) produces a stationary wave between the loudspeaker and the reflector.
 - This results in a wave with maximum displacement at antinodes, and zero amplitude at nodes.
- 3. A microphone connected to the oscilloscope is moved along the straight line between the loudspeaker and the reflector.
- 4. At nodes, minimal signal is displayed, while at antinodes, maximum signal is displayed the average distance d between two adjacent antinodes can be determined, and thus the wavelength.

$$\lambda = 2d \implies v = f(2d)$$

11.3 Intensity

From simple harmonic motion, we understand that the total energy associated with an oscillatory motion is proportional to the square of its amplitude.

$$E = \frac{1}{2}m\omega^2 x_0^2 = \frac{1}{2}m(2\pi f)^2 x_0^2$$

Definition 11.15:

The intensity I of a wave is the rate of energy transmitted per unit area perpendicular to the wave velocity.

$$I = \frac{E/t}{A} = \frac{W}{A}$$

We note that for amplitude x_0 and distance travelled by the wave r,

$$I \propto {x_0}^2$$
 and $I \propto {1 \over r^2}$

Since $I \propto E$ and $E \propto f^2 x_0^2$, then for a constant frequency f,

 $I \propto x_0^2$

11.3.1 Inverse Square Law

Consider a point source which emits energy with power P. Energy is transferred radially outward in three dimensions, carried on an expanding spherical surface.

At a distance r from the source,

$$I = \frac{P}{A} = \frac{P}{4\pi r^2} \implies I \propto \frac{1}{r^2} \text{ (3D)}$$

This is known as the **inverse square law**, where the observed intensity of the wave is inversely proportional to the square of the distance from the source.

Notably, the inverse square law **does not hold for two-dimensional transmission**. For a point source that emits energy two-dimensionally, the wave propagation can be encapsulated within a cylinder of height $h = 2x_0$. At a distance r from the source,

$$I = \frac{P}{A} = \frac{P}{2\pi rh} \implies I \propto \frac{1}{r} (2D)$$

Example 11.1

A constant power source of 500 watts emits light uniformly in all directions.

- 1. Calculate the intensity of the light detected by a man located 3.0m from the source.
- 2. The power of the source is now halved. In order to detect the same intensity as before, determine the distance of the man from the source.

For part (a),

$$I = \frac{P}{4\pi r^2} = \frac{500}{4\pi (3.0)^2} = \boxed{4.42 \text{ W m}^{-2}}$$

For part (b),

$$\frac{P}{4\pi r^2} = \frac{P'}{4\pi R^2}$$
$$R^2 = \frac{P'}{P}r^2 = \frac{1}{2}(3.0)^2$$
$$R = \boxed{2.12 \text{ m}}$$

11.4 Polarisation

Definition 11.16: Plane Polarisation

If the oscillations in a **transverse wave** are confined to **one direction only**, in a plane normal to the direction of energy transfer, the wave is said to be **polarised** in that direction.

An **ideal polariser** passes all incident light parallel to its polarising axis, and blocks all light perpendicular to this axis.



Since the vertical and horizontal components of random incident light are equal on average, the intensity I of emerging polarised light from an unpolarised light of intensity I_0 is

$$I = \frac{1}{2}I_0$$

It is **not possible to polarise sound waves**, as they are longitudinal, having no oscillations in the plane normal to the direction of transfer of energy of the wave.

11.4.1 Malus's Law

Definition 11.17: Malus's Law

Malus's law states that when an ideal polariser is placed in a polarised beam of light, the intensity I of the light that passes through is

$$I = I_0 \cos^2 \theta$$

where I_0 is the initial intensity of the light and θ is the angle between the light's initial polarisation direction and the axis of the polariser.

This is because when two polarisers are placed along axes varied by an angle θ , only the parallel component of amplitude $A \cos \theta$ is transmitted past the second polariser.

$$I_0 \propto A^2, \ I \propto (A \cos \theta)^2 \implies \frac{I}{I_0} = \cos^2 \theta$$

 $\implies I = I_0 \cos^2 \theta$

12 Superposition

12.1 Superposition Principle

Definition 12.1: Superposition Principle

The **superposition principle** states that when two or more waves of the same type meet at a point at the same time, the **displacement** of the resultant wave is the **vector sum** of the displacements of the individual waves at that point in time.

Two waves must be of the same type in order for the principle of superposition to apply.

12.2 Interference

12.2.1 Coherence

Definition 12.2: Coherence

Two sources are said to be **coherent** if the waves produced by the two sources have a **constant phase difference**.

The satisfaction of coherence implies the propagation of an identical frequency.

12.2.2 Constructive and Destructive Interference

Definition 12.3: Interference

Interference occurs when two or more wvaes overlap to produce a resultant wave pattern.

Constructive interference occurs when two waves **meet in phase**; the resultant amplitude is the sum of the individual amplitudes of the waves.

Destructive interference occurs when two waves **meet in anti-phase**; the resultant amplitude is zero.

The distance along any path from source to receiver is called the **path length** r. The **path difference** between two waves is simply the absolute difference between their path lengths.

Constructive interference occurs when

- the path difference $\Delta r = n\lambda$, $n \in \mathbb{Z}$; or
- the phase difference $\phi = 2k\pi, k \in \mathbb{Z}$

Conversely, destructive interference occurs when

- the path difference $\Delta r = (n + \frac{1}{2})\lambda$, $n \in \mathbb{Z}$; or
- the phase difference $\phi = (2k+1)\pi, k \in \mathbb{Z}$

The above is true if both waves are **initially in phase**. If the two waves start in anti-phase instead with $\phi = \pi/2$, the above formulae will **swap** between constructive and destructive interference.

12.3 Stationary Waves

Definition 12.4: Stationary Wave

A stationary wave (or standing wave) is formed when two progressive waves of the same type of equal amplitude, equal frequency, equal speed ravelling in opposite directions meet and undergo superposition with each other.

Note that vibrational energy is not transmitted across the wave (hence the name "stationary"). Every stationary wave has amplitudes of oscillation varying from maximum at **antinodes** to zero amplitude at **nodes**.



The distance between adjacent antinodes/nodes is $\lambda/2$, whereas the distance between a node and an adjacent antinode is $\lambda/4$.

12.3.1 Two Fixed Ends

Waves in stretched strings contain the following circumstance — the ends of a string are fixed with zero displacement.



This results in a number of discrete oscillatory patterns, called **normal modes**. These modes are also known as **harmonics**.



Suppose a standing wave is formed over a stretched string of length L. Then, for the *n*th normal mode, the wavelength and frequency of the wave is given by

$$\lambda_n = \frac{2L}{n} \implies f_n = \frac{nv}{2L} = nf_1$$

12.3.2 1 Fixed End, 1 Free End

We often examine waves under boundary conditions in air columns — a closed end of a pipe is a **displacement node**. Recall that pressure is 90° out of phase with displacement, hence it is also a *pressure antinode*. This is similar for the open end of a pipe.



In a pipe closed at one end, the natural frequencies form a harmonic series that includes only odd integer multiples of the fundamental frequency. For a pipe of length L,

$$\lambda_n = \frac{4L}{n} \implies f_n = \frac{nv}{4L}$$

12.3.3 2 Free Ends



In a pipe **open at both ends**, the natural frequencies form a harmonic series that includes *all integer multiples* of the fundamental frequency.

$$\lambda_n = \frac{2L}{n} \implies f_n = \frac{nv}{2L}$$

12.4 Diffraction

Definition 12.5: Diffraction

Diffraction is the spreading of a wave as it passes through a gap or around an obstacle.



In general, diffraction is most significant when the size of the width is of the same order of magnitude as the wavelength of the wave.

12.4.1 Single-Slit Diffraction

For a **single-slit diffraction** with slit width b, dark fringes occur at angles θ given by the following equation.

$$\sin \theta = m \frac{\lambda}{b}, \ m \in \mathbb{Z}$$

The figure below shows a typical set-up for single-slit diffraction.



Questions will likely test on what occurs to the diffraction pattern when the fundamental setup is modified. If so, talk about the (1) separation of fringes, (2) amplitude of waves, and (3) overlapping of diffracted waves.

The single slit equation fails with $m\lambda/b > 1$. For such values of m, no diffraction pattern can be observed.
12.4.2 Rayleigh Criterion

Definition 12.6: Rayleigh Criterion

The **Rayleigh criterion** states that two patterns are *just* resolved when the central maximum of one pattern lies on the first minimum of the other pattern.

$$\theta_{\min} \approx \frac{\lambda}{b}$$

where θ_{\min} is the minimum angle between two rays.

12.4.3 Double-Slit Diffraction

Definition 12.7: Conditions for Double-Source Interference

For double-source interference fringes to be **observable**,

- waves must **meet**
- waves must be **coherent**
- waves have (approximately) equal amplitudes
- transverse waves must be either unpolarised or polarised in the same plane
- the slit separation d is of the same order as wavelength λ .

Young's Double-Slit Experiment

In the case of **Young's double-slit experiment**, for slit separation a, slit-to-screen distance D, and fringe separation x,

$$\lambda = \frac{xa}{D}$$

Young's double-slit experiment consists of a light being passed through a single slit, and then a double slit to form an interference pattern.



The following diagram shows a visualisation of the wavelength propagation during the double-slit experiment.



Single-Slit Envelope

Since the experiment consists of a double slit in front of a single slit, the primary effects of single-slit diffraction will be observed **over** that of the double-slit interference pattern.

The overall intensity of a double-slit interference pattern is **modulated** by the overarching single-slit envelope.



Without the single-slit envelope, the relative intensities of the bright fringes will instead be constant.

12.4.4 Diffraction Grating

A diffraction grating consists of a large number of equally-spaced lines, each of which are capable of diffracting incident light.

In a diffraction grating with slit separation d, for the nth order maximum, the path difference is given by

$$d\sin\theta = n\lambda$$

Diffraction gratings are usually specified by the number of lines N per unit length.

$$d = \frac{\text{unit length}}{N}$$

Part V Electricity and Magnetism

13 Electric Fields



A map summarising all the relations between different electrostatic quantities is shown below.

13.1 Electric Force

Definition 13.1: Coulomb's Law

Coulomb's law states that the electric force between two point charges is directly proportional to the product of the charges, and inversely proportional to the square of the distance between them.

$$F = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r^2}$$

where q_1 and q_2 are the charges (in coulombs, C), r is their separation, and ϵ_0 is the permittivity of free space. Note that $1/(4\pi\epsilon_0) = 9.0 \times 10^9$ N m² C⁻².

The direction of the force is along the line joining the two point charges. This relation is **only applicable** if

- the charges are point charges, or
- if the two charged bodies are separated far apart such that the size of each charged body is negligible compared to their separation.

13.2 Electric Field

Definition 13.2: Electric Field

An electric field is a region of space within which there is an electric force acting on a charged object placed in that field.

The direction of the electric field is the direction that an electric force would act upon a positive test charge.

13.2.1 Electric Field Strength

Definition 13.3: Electric Field Strength

The electric field strength E at a point in the field is defined as the electric force per unit positive charge experienced by a charge placed at that point.

$$E = \frac{F}{q} = \frac{Q}{4\pi\epsilon_o r^2}$$

If a particle of charge q experiences an electric force of F_E when placed at a certain point in the field caused by another charge q, the strength of the electric field caused by charge q at that point is given by the equation above.

Consider a point charge Q. If another point charge q is placed a distance r from Q, the electric force exerted by Q on q is given by Coulomb's law.

$$F = \frac{1}{4\pi\epsilon_0} \frac{Qq}{r^2}$$

Thus, the electric field strength due to a point charge is given by

$$E = \frac{F}{q} = \frac{Q}{4\pi\epsilon_o r^2}$$

13.2.2 Field Lines

An electric field may be represented by lines of force known as **electric field lines**, which indicate the **direction of the force** a stationary positive charge would experience if placed at that point.

Some basic fields of electric field lines are listed below.

- The **direction** of the electric force is **tangential** to the field line at each point it is the direction of the force that a small stationary positive test charge would experience.
- The spacing between the lines indicates field strength. A stronger field would have more closely spaced lines.
- Electric field lines either originate on positive charges or come in from infinity, and either terminate on negative charges or extend out to infinity.
- The number of lines originating from a positive charge or terminating on a negative charge must be proportional to the magnitude of the charge.
- They do not intersect.
- In a uniform field, all lines are parallel and equally spaced apart.
- Field lines must touch the surface of charged conductors at a right angle.

For an isolated positive charge, its field lines point radially outward. Conversely, for an isolated negative charge, its field lines point radially inward.



For two charges of equal magnitude, they cancel out. The number of field lines leaving the positive charge must be equal to the number of field lines terminating at the negative charge.



Similarly, for a positive charge +2q and a negative charge -q, two field lines must leave the positive charge for every line that terminates on the negative charge



13.2.3 Charged Parallel Plates

Consider a pair of charged parallel plates separated by a distance d with potential difference ΔV , as shown below.



The uniform electric field E between both plates has a field strength with magnitude

$$E = \frac{|\Delta V|}{d} \implies F = \frac{q|\Delta V|}{d}$$

Note that the direction of the electric field points from the plate with the higher electric potential to the plate with the lower electric potential.

13.2.4 Motion of Charged Particles

Within a uniform electric field, the force on a charged particle anywhere in the field is **constant**, meaning that the charged particle has **constant acceleration**.

Depending on the relative direction of electric field to its motion, it could be in either linear motion or projectile motion. In both cases, under the electric force, a charged particle of mass m will accelerate with an acceleration a.

$$\sum F = ma \implies qE = ma \implies \frac{q|\Delta V|}{d} = ma \implies a = \frac{q|\Delta V|}{md}$$

As the charged particle has constant acceleration, its kinematic quantities can be modelled using the **kinematic equations of motion**. For t, the equation s = ut is commonly used along an axis where the charged particle does not experience any acceleration.

Example 13.1

An electron is projected into the space between two charged plates of length 5.0 cm, as shown in the diagram below.



The electric field strength E is 3.5×10^4 N C⁻¹ and the velocity u of the electron is 3.2×10^7 m s⁻¹. Neglecting gravitational effects, determine

- 1. the distance it deviates towards the positively-charged plate, and;
- 2. its speed just as it leaves the electric field.

To determine vertical deviation, we observe that the electron experiences no horizontal acceleration. Hence,

$$s_x = u_x t \implies t = \frac{0.05}{3.2 \times 10^7} = 1.56 \times 10^{-9} \text{ s}$$

From Newton's second law,

$$F = ma = qE \implies a = \frac{qE}{m}$$
$$\implies a = \frac{(1.60 \times 10^{-19})(3.5 \times 10^4)}{9.11 \times 10^{-31}} = 6.15 \times 10^{15} \text{ m s}^{-2}$$

Using kinematic equations,

$$s_y = u_y t + \frac{1}{2} a_y t^2$$

= 0 + $\frac{1}{2} (6.15 \times 10^{15})^2 (1.56 \times 10^{-9})^2$

This gives us the vertical deviation of the electron.

$$s_y = 7.48 \times 10^{-3} \text{ m}$$

To find the final velocity of the electron, we note that $v_x = 3.2 \times 10^7 \text{ m s}^{-1}$. Finding the velocity's vertical component,

$$v_y = u_y + a_y t = 0 + (6.15 \times 10^{15})(1.56 \times 10^{-9})$$

= 9.59 × 10⁶ m s⁻¹

The velocity is hence

$$v = \sqrt{v_x^2 + v_y^2} = 3.34 \times 10^7 \text{ m s}^{-1}$$

13.3 Electric Potential

Definition 13.4: Electric Potential

The electrical potential, V, at a point is the **work done per unit positive charge** by an external agent to bring a small test charge q from infinity to that point, without producing any acceleration.

$$V = \frac{W}{q} = \frac{1}{4\pi\epsilon_0} \frac{Q}{r}$$

where V is the electric potential at a distance r from the centre of Q.

Electrical potential is a *scalar* quantity with S.I. unit volt (V) or joule per coulomb.

13.3.1 Equipotential Lines

Electric potential in an electric field can be represented by **equipotential lines** indicated by a dashed line. Equipotential lines are lines that join points in an electric field with the **same electric potential**. They meet **perpendicular** to the electric field lines.

No work is done by an external force when a charge is moved **along** an equipotential line, because the electric force is always perpendicular to said line. Work is only done if the charge has some component of its motion parallel to the electric force.

13.3.2 Electric Potential Gradient

Definition 13.5: Electric Potential Gradient

The electric potential gradient at a point in an electric field is numerically equal to the electric field strength E.

$$E = -\frac{dV}{dr}$$

The term dV/dr is known as the potential gradient. Hence, the field strength at a point in the field is the negative derivative of electric potential V with respect to r. The negative sign indicates the direction of the electric field, which **points towards the decreasing electric potential**.

13.4 Electric Potential Energy

Definition 13.6: Electric Potential Energy

When two point charges q_1 and q_2 have a separation r, the electric potential energy U of the system of two charges is given by

$$U = \frac{1}{4\pi\epsilon_0} \frac{q_1 q_2}{r} = qV$$

Where q_1 and q_2 are like charges,

- U is always positive.
- As $r \to 0$, $U \to \infty$. As $r \to \infty$, $U \to 0$.
- U increases as they come closer, since work is done on the repelling system.

Where q_1 and q_2 are **unlike charges**,

- U is always negative.
- As $r \to 0$, $U \to -\infty$. As $r \to -\infty$, $U \to 0$.
- U decreases as they come closer, since work is done by the attracting system.

U is a shared property between two charges q_1 and q_2 , arising as a consequence of the interaction between these two bodies.



For a system of several charges containing q_1, q_2, \dots, q_n , the total electric field at each point is the vector sum of the fields due to the individual charges, and the *total work done on a single point charge* Q during any displacement is the sum of the contributions from the individual charges.

$$U = \frac{Q}{4\pi\epsilon_0} \left(\frac{q_1}{r_1} + \frac{q_2}{r_2} + \dots + \frac{q_n}{r_n} \right)$$

As for a system of several charges, we can find the *total electric potential energy of the system* by calculating U for every *pair* of charges. Expressed in sigma notation, the generalised equation for the total electric potential energy of a system is

$$\sum U = \frac{1}{4\pi\epsilon_0} \sum_{i < j} \frac{q_i q_j}{r_{ij}}$$

In particular, the figure below depicts a system of three point charges.



Enumerating through all pairs of charges, the total electric potential energy of this system is

$$\sum U = \frac{1}{4\pi\epsilon_0} \left(\frac{q_1q_2}{r_{12}} + \frac{q_2q_3}{r_{23}} + \frac{q_1q_3}{r_{13}} \right)$$

14 Current of Electricity

Without electricity, there can be no art.

— Nam June Paik

14.1 Charge

Charge is a property possessed by some elementary particles, most notably electrons and protons. Electrical charge (commonly represented by Q) has a S.I. unit of coulomb (C).

Charge comes in two varieties — **positive and negative**, which neutralise one another if brought together in equal quantities. Objects that have an electrical charge exert electrostatic forces on each other.

The elementary charge, $e = 1.60 \times 10^{-19}$ C, is the charge of one proton.

14.2 Electric Current

Definition 14.1: Electric Current

Electric current is the rate of flow of charge. It has the S.I. unit of ampere (A).

$$I = \frac{dQ}{dt} \implies \langle I \rangle = \frac{Q}{t}$$

Electric current consists of *charges in motion* from one region to another. When this motion takes place within a conducting path in a closed loop, the path is an **electric circuit**.

In metallic conductors, current is caused by the flow of electrons. However, by convention, the direction of current is the direction of positive charges' movement.

14.2.1 Microscopic Model of Current

Definition 14.2:

Current is the rate of flow of charge, and is thus the **number of charge carriers** passing through **per unit time** multiplied by the **charge per carrier**.

$$I = nAvq$$

where n is the charge carrier density, A is the cross-sectional area of the conductor, v is the drift velocity, and q is the charge per carrier.

Collisions between electrons and metal ions caused by thermal energy are frequent and random, but thermal motion itself does not carry the electron any distance along the wire.

Rather, due to the **potential difference** applied across the conductor, the charge carriers gain an additional drift motion that carries them along the conductor ($\approx 10^{-4} \text{ m s}^{-1}$), causing charge to be transferred. The direction of this drift is determined by field lines from the cell.

14.3 Voltage

14.3.1 Potential Difference

Definition 14.3: Potential Difference

The **potential difference** between **two points** in a circuit is defined as the work done per unit charge when *electrical energy is converted to non-electrical energy* when the charge passes from one point to the other.

potential difference =
$$\frac{W}{Q}$$

where W is the energy transformed from electrical to non-electrical energy when a charge of Q flows in the part of the circuit.

When a current passes through an electrical device, electrical energy is converted into other forms of energy (e.g. heat, light, mechanical energy).

The amount of electrical energy converted per unit charge is called the **electrical potential difference**.

14.3.2 Electromotive Force

Definition 14.4: Electromotive Force

The **electromotive force** (abbreviated **e.m.f.**) of a source can be defined as the work done per unit charge when *non-electrical energy is converted into electrical energy* when the charge is moved around a complete circuit.

In order to maintain an electric current in an electrical circuit, a potential difference across the ends of the entire circuit is needed. To achieve this, the ends of the electrical circuit are connected to opposite terminals of a battery.

This potential difference maintained by the battery is known as its **electromotive force**, a measure of work done per unit charge by the battery.

Electromotive force	Potential difference
Refers only to the source.	Refers to any two points in an electrical circuit.
Considers the amount of non-electrical energy converted into electrical energy per unit charge passing through the source.	Considers the amount of electrical energy con- verted to non-electrical energy per unit charge passing from one point to another.
It is a source of energy that <i>exists irregardless</i> of whether a current is flowing.	It can only exist if current is flowing in the electrical current.

14.4 Resistance

Definition 14.5: Resistance

The **resistance** of a component is defined as the ratio of the potential difference across the component to the current passing through it.

$$R = \frac{V}{I}$$

The resistance of a conductor is a measure of its opposition of flow of current through itself — it is *a property of a conductor*.

14.4.1 Ohm's Law

Definition 14.6: Ohm's Law

Ohm's Law states that the current flowing through a conductor is directly proportional to the potential difference applied across the conductor, provided that physical conditions remain constant.

 $I \propto V$

14.4.2 I-V Characteristics

The I-V graph of a material, obtained experimentally, allows the resistance of the material to be determined for various values of I or V.

When the current passes through a material increases, the **temperature** of the material is likely to **increase**. When the latter occurs, two main changes occur.

- 1. The charge concentration n increases, which reduces the resistance of the material.
- 2. The **thermal vibrations of the lattice atoms** increases, which **increases** the resistance of the material.

Metallic Conductor



I/V graph of a metallic conductor at constant temperature.

Since the conductor is maintained at constant temperature, the charge concentration n is **fixed** and the amplitude of atomic vibration and the rate of collisions with the atoms **remains unchanged**.

Thus, the resistance remains a constant and the conductor is said to be **ohmic**.



I/V graph of a filament lamp.

Filament Lamp

As V increases, I increases initially. Further increase of V causes a less-than-proportionate increase in the current.

As the temperature increases, n will *not* vary significantly, but the **amplitude of atomic vibrations increases**, and so does the number of collisions with the atoms per unit time. Since the increase in the rate of interaction of electrons with the lattices **predominates over** the increase of n, the overall effect is that R increases.

Semiconductor Diode



I/V graph of a semiconductor diode.

Considering the **forward-biased** region,

- As V increases, the temperature of the semiconductor increases.
- Electrons in the semiconductor are more likely to have sufficient energy to escape from a particular atom if the temperature is higher, hence *n* increases significantly.
- The rate of interaction of electrons with the vibrating atoms also increases.
- However, as the increase in *n* **predominates over** the rate of interactions of electrons with the lattice, the overall effect is that *R* **decreases**.

If the forward voltage is greater than a threshold value (0.7V for silicon diodes), then a large current will pass through the diode.

For the **reverse-biased region**, there is no current flow through the diode until the breakdown voltage (at least 50V).

NTC Thermistor



I/V graph of a NTC thermistor.

For a **negative temperature coefficient** (abbreviated **NTC**) thermistor, its resistance **falls** at the temperature **rises** (i.e. its resistance is inversely proportional to temperature).

As the temperature increases, the charge concentration n of the material increases, hence reducing the resistance. As such, its I/V characteristic is the same as that for a semiconductor diode for positive values of V and I.

14.4.3 Resistivity

Definition 14.7: Resistivity

For a conductor of resistivity ρ , length l, and cross-sectional area A, its resistance is given by

$$R = \rho \frac{l}{A}$$

The resistance of a conductor depends on

- the nature of the material;
- the size of the sample (length and cross-sectional area); and
- the temperature of the sample.

Consider the analogy of water flow — a longer pipe offers more resistance, while a wider pipe offers less resistance than a narrow pipe. Hence, one would expect electrical resistance to be greater with a longer and thinner conductor.

The constant of proportionality ρ , known as **resistivity** (dependent on temperature), is governed by the nature of the material. Metals generally have low resistivity values ($\approx 10^{-8} \Omega m$), whereas insulators have high resistivity values ($10^{13} - 10^{16} \Omega m$).

14.5 Electrical Power

Definition 14.8: Electrical Power

Electrical power, denoted by P is electrical energy dissipated by a conductor per unit time. Watt's law provides the following relationships between power, voltage, and current.

$$P = VI = I^2 R = \frac{V^2}{R}$$

14.5.1 Power Rating

The rated power is the rate at which energy is used (power consumption) by a device when the device is operating at the rated potential difference across it.

For example, when an electrical device is rated 100W and 220V, it means that when a potential difference of 220V is applied across the terminals of the device, the device dissipates 100W of power.

14.6 Internal Resistance

Consider a simple circuit consisting of a cell and a resistor.



In an **ideal circuit**, the connecting wires would have no resistance, and the potential difference V across the cell terminals is **equal** to the electromotive force E of the cell.

However, real cells always have some internal resistance r — not all electrical energy generated is available to the external load R.

Some energy is lost as heat within the source due to its internal resistance, hence the **terminal p.d.** is **not equal** to the e.m.f. of the source.

A real battery can be modelled as (one ideal cell or a combination of ideal cells) connected in series to a resistor r.

The power supplied by the ideal source is given by

$$P_s = IE$$

In the internal resistance r, there is power dissipated as heat.

 $P_r = I^2 r = I V_r$ (dissipated as heat)



In the external load R,

$$P_R = I^2 R = I V_R$$

By the principle of conservation of energy,

$$P_s = P_r + P_R$$
$$IE = I^2 r + I^2 R$$
$$\implies \boxed{E = I(r+R)}$$

Alternatively,

$$P_{s} = P_{r} + P_{R}$$

$$IE = IV_{r} + IV_{R}$$

$$E = Ir + V_{R}$$

$$\implies V_{R} = E - Ir$$

Here, V_R is equal to the terminal p.d. across the circuit.

When a current I is flowing, the voltage drops by Ir across the internal resistance and hence the remaining voltage across the battery will be $V = E - Ir = V_R$.



14.6.1 Maximum Power Theorem

Definition 14.9: Maximum Power Theorem

The **maximum power theorem** states that maximum power is supplied to the external circuit when the **resistance** of the external circuit is **equal** to the **internal resistance** of the cell.

Proof. Consider a practical source with e.m.f. E and internal resistance r connected in series with an electrical device of resistance R.

The current passing through the circuit is given by

$$I = \frac{V}{R} = \frac{E}{R+r}$$

Thus, the power delivered to the device is

$$P = I^2 R = \left(\frac{E}{R+r}\right)^2 R$$

To find maximum P, we let the derivative be zero.

$$\frac{dP}{dR} = 0 \implies \frac{E^2(R+r)^2 - 2E^2R(R+r)}{(R+r)^4} = 0$$
$$\implies E^2(R+r)^2 - 2E^2R(R+r) = 0$$
$$\implies R+r = 2R$$
$$\implies \boxed{R=r}$$

Hence, maximum power is dissipated through the circuit when the resistance of the external circuit is equal to the internal resistance of the cell.

When operating an electrical device at maximum power, the output efficiency of the source is

$$\eta = \frac{\text{useful energy}}{\text{total energy}} = \frac{I^2 R}{I^2 (R+r)} = \frac{R}{R+r} = \frac{R}{2R} = 50\%$$

Half the amount of power it generates is lost due to the internal resistance of the cell.

15 D.C. Circuits

15.1 Symbols

The following image shows some common circuit symbols as specified by the Association of Scientific Education.



Ideal voltmeters have infinite internal resistance and zero current, but in practice, it draws a small current and thus reads a potential difference smaller than the actual value. Voltmeters are always connected **in parallel** across the component to be measured.

Ideal ammeters have zero internal resistance and zero potential difference, but in practice, it has a finite potential difference across its ends and thus reads a current smaller than the actual value. Ammeters are always connected **in series** along the network where the current is to be measured.

15.2 Kirchhoff's Laws

Kirchhoff's circuit laws are two equalities that pertain to electrical current and potential difference, and are crucial in the field of circuit analysis.

15.2.1 Kirchhoff's Current Law

Definition 15.1: Kirchhoff's Current Law

Kirchhoff's current law states that the sum of currents entering any junction in an electric circuit is always equal to the sum of current leaving that junction.

$$\sum_{i=1}^{n} I_i = 0 \text{ (for a junction)}$$

Kirchhoff's current law is a direct result of the principle of conservation of charge. The total charge that enters a junction per unit time must be equal to the total charge that leaves the same junction per unit time.



In the circuit above, the three currents are related by $I = I_1 + I_2$.

15.2.2 Kirchhoff's Voltage Law

Definition 15.2: Kirchhoff's Voltage Law

Kirchhoff's voltage law states that in any closed loop in an electric circuit, the total electromotive force supplied E equals to the total potential difference in that loop.

$$\sum_{i=1}^{n} V_i = 0 \text{ (for a loop)}$$

The principle of conservation of energy imlpies that the electrical energy produced by the source should be equal to the sum of electrical energy consumed by all the components.



In the circuit above, considering energy,

energy from source = energy used by resistors

$$(IE)t = (I^2R_1)t + (I^2R_2)t$$

 $E = IR_1 + IR_2$
 $E = \boxed{V_1 + V_2}$

15.3 Effective Resistance

For resistors connected in series,

$$R_{\rm eff} = R_1 + R_2 + \cdots$$

The effective resistance of resistors in series is **always larger** than the **largest resistance** in the circuit.

For resistors connected in parallel,

$$R_{\text{eff}} = \left(\frac{1}{R_1} + \frac{1}{R_2} + \cdots\right)^{-1}$$

The effective resistance of resistors in parallel is **always smaller** than the **smallest resistance** in the circuit.

15.4 Potential Divider

A **potential divider** is an arrangement of resistors which is used to obtain a fraction of the potential difference provided by a battery.

The circuit shows a simple potential divider, consisting of two resistors of resistances R_1 and R_2 connected to a cell with e.m.f. E.



V' here is the potential difference across R_1 .

$$V' = IR = \left(\frac{E}{R_{\text{eff}}}\right)R_1 = \left(\frac{E}{R_1 + R_2}\right)R_1$$

To supply a continuously variable potential difference from zero to the full voltage of the supply E, a resistor with a sliding contact may be used, as shown below.



15.4.1 Potential

Every point in a circuit has a **potential**.

- Two points have equal potential if they are connected directly by a zero-resistance wire; there is **no** potential difference between them.
- If two points are separated by a component with resistance, they have a **non-zero** potential difference (unless there is no current).

For potential difference to exist, the component must either be an e.m.f. source, or have both resistance and current flowing through it.

15.5 Potentiometer

Consider the setup below.



The circuit consists of a cell with e.m.f. E, a resistor R_s , a resistance wire of length AB. Connected in parallel to the circuit is another circuit with unknown potential difference, a galvanometer, and a sliding contact at C.

The sliding contact will have a point where **there is no current in the galvanometer**. This point is known as the balance point.

Let the balance point be C. The length AC is known as the **balance length**.

The essence is that at the balance point, the p.d. across AC is equal to the p.d. across the unknown circuit.

We assume that the wire has uniform cross-sectional area, constant potential difference (with time), and constant length (with time).

For a uniform wire of length $L, R \propto L$. Since the same current flows through the entire wire,

$$V_{\rm AC} = \frac{R_{\rm AC}}{R_{\rm AB}} \times V_{\rm AB} = \frac{L_{\rm AC}}{L_{\rm AB}} \times V_{\rm AB} = \frac{V_{\rm AB}}{L_{\rm AB}} \times L_{\rm AC} = \boxed{kL_{\rm AC}}$$

where k is the **potential per unit length** of the resistance wire AB.

15.5.1 Comparison of Electromotive Force

Suppose you have the setup below. You are trying to find the ratio of E_1 to E_2 .



At the balance length,

$$E_1 = kl_1$$
 and $E_2 = kl_2 \implies \frac{E_1}{E_2} = \frac{l_1}{l_2} \implies \left| E_1 = \frac{l_1}{l_2} E_2 \right|$

The setting of the variable resistor must be the same for the two cells so that the potential difference across wire XY is the same.

15.5.2 Measuring Electromotive Force

Consider the setup below.



A potentiometer has a resistance wire AB of length L and resistance R, powered by a cell of e.m.f. E, alongside a resistor of resistance R_s .

With an unknown e.m.f. E_1 in the branch circuit, the balance point is C.

The p.d. across wire AB is

$$V_{\rm AB} = IR = \frac{R}{R + R_s} \times E = \frac{RE}{R + R_s}$$

Using the potentiometer principle,

$$E_1 = \frac{L_{\rm AC}}{L_{\rm AB}} \times V_{\rm AB} = \boxed{\frac{L_{\rm AC}}{L} \left(\frac{RE}{R+R_s}\right)}$$

15.5.3 Determining Internal Resistance

To determine the internal resistance of a cell, consider the following circuit.



Switch S is open.

When switch S is **opened**, there is **no current** passing through R_2 . The balance point is C with balance length L_1 .

From this alone, because there is no current passing through r, we can find E_1 with ease.

$$E_1 = \frac{L_{\rm AC}}{L_{\rm AB}} \times V_{\rm AB} = \frac{L_1}{L} \left(\frac{R_{\rm AB}E}{R_{\rm AB} + R_1} \right)$$

OK.

Now, we shall close S.



Switch S is closed.

When switch S is closed, current passes through R_2 . The new balance point is D with balance length L_2 .

Now, because there is now current in the bottom circuit, we can find the terminal p.d. V_T across E_1 .

$$V_T = \frac{L_2}{L} \left(\frac{R_{\rm AB} E}{R_{\rm AB} + R_1} \right)$$

The terminal p.d. V across E_1 will also be equal to the p.d. across resistor R_2 . Using V = IR, we can find the current flowing through R_2 .

$$V = IR \implies I = \frac{V_T}{R_2}$$

Using the equation V = E - Ir, we can find the internal resistance r.

$$V = E - Ir \implies r = \frac{E - V_T}{I}$$

16 Electromagnetism

The world may be utterly crazy And life may be labour in vain; But I'd rather be silly than lazy, and would not quit life for its pain.

— James Clerk Maxwell, c. 1858

16.1 Magnetic Fields

Definition 16.1: Magnetic Field

A magnetic field is a region of space within which a non-contact magnetic force

- must act on a permanent magnet or ferromagnetic material, and
- *might* act on a current-carrying conductor or a moving charge.

The strength of a magnetic field is expressed by the **magnetic flux density** \vec{B} , a vector quantity with the unit tesla (T).

16.1.1 Magnetic Field Lines

The following are characteristics of magnetic field lines.

- They come out of north poles and go into south poles.
- The tangent of a field in space shows the direction of force that a "free" magnetic monopole will experience at that point.
- Stronger fields are represented by a denser concentration of lines; conversely, weaker fields are represented by lines that are further apart.

Magnetic field lines that point **into the paper** are denoted by **crosses**, whereas field lines that point **out of the paper** are denoted by **dots**.



16.1.2 Ampere's Right-Hand Grip Rule

Ampere's right-hand grip rule provides a visualisation for the geometrical relationship between magnetic fields and direction of current flow.



This can be used for straight wires, flat circular coils, and solenoids.

16.1.3 Fleming's Left-Hand Rule

Current-carrying conductors and moving charged particles in a magnetic field might experience a force. This force is **always perpendicular** to the direction of the current and the direction of the magnetic field.

Fleming's left-hand rule provides a handy visualisation for the directions of the magnetic force, magnetic field, and electrical current.



16.1.4 Magnetic Field Intensification

A ferrous core can increase the magnetic flux density inside a **long solenoid** compared to an air core solenoid.

This is because the magnetic permeability of the ferrous core $(k\mu_0)$ is greater than the magnetic permeability of air (μ_0) .

Other methods to increase the magnetic flux density of the long solenoid include

- increasing the current I flowing through the long solenoid, and
- increasing the number of turns per unit length n of the solenoid.

16.2 Magnetic Flux Density

Definition 16.2: Magnetic Flux Density

The magnetic flux density *B* of a magnetic field is defined as the magnetic force per unit current per unit length acting on a straight current-carrying conductor placed perpendicular to a uniform magnetic field.

$$B = \frac{F}{IL\sin\theta}$$

where B is the magnetic flux density, F is the magnetic force acting on the conductor, I is the current, L is the length of conductor, and θ is the angle between $\vec{\mathbf{B}}$ and $\vec{\mathbf{F}}$.

The S.I. unit of magnetic flux density is the tesla (T). For all following definitions, $\mu_0 = 4\pi \times 10^{-7}$ H m⁻¹ is the permeability of free space.

16.2.1 Long Straight Wire

The magnetic flux density of a current-carrying long straight wire is given by

$$B = \frac{\mu_0 I}{2\pi d}$$

where I is the current through wire and d is the perpendicular distance of the point in question from the wire.

16.2.2 Flat Circular Coil

The magnetic flux density of a flat circular coil of radius r with N coil loops, carrying a current I, is given as

$$B = \frac{\mu_0 NI}{2r}$$

16.2.3 Solenoid

The magnetic flux density of an (infinitely) long solenoid carrying a current I is given by

$$B = \mu_0 n I$$

where n = N/L is the number of turns per unit length of the solenoid.

16.3 Magnetic Force

The magnitude of the magnetic force acting on a **current-carrying conductor** placed at an angle θ to the magnetic field can be expressed as

$$\vec{\mathbf{F}} = \vec{\mathbf{B}} \times I \vec{\mathbf{L}} \implies F = BIL \sin \theta$$

In the above, we must stress that the magnetic force is acting on the **electrons** flowing through the conductor. Particularly when the magnetic force is perpendicular to the direction of electron flow, the force on these electrons is *transmitted to the wire* upon collision.

The magnetic force acting on a **moving charged particle** of charge Q and speed v is given by

$$\vec{\mathbf{F}} = \vec{\mathbf{B}} \times q\vec{\mathbf{v}} \implies F = Bqv\sin\theta$$

16.3.1 Parallel Current-Carrying Conductors

If two long wires run parallel to, and near each other,

- if both their currents flow in the same direction, the wires will attract each other;
- if their currents flow in **opposite directions**, the wires will **repel** each other.

16.3.2 Motion of Charged Particles

When a charged particle is projected at a right angle into a magnetic field, notice that the magnetic force F must always be perpendicular to the particle's velocity v.

Since, the distance travelled in the direction of the force is zero, magnetic force does no work on a charged particle.

To put it more specifically, since F is of constant magnitude and is always perpendicular to v, the charged particle undergoes *circular motion*.



If the magnetic field is pointing into the paper,

- positively charged particles travel counterclockwise,
- negatively charged particles travel clockwise.

The opposite holds true if the magnetic field is pointing out of the paper instead.

Now, we will analyse the Newtonian mechanics behind the circular motion caused by magnetic forces. By Newton's second law,

$$\sum \vec{\mathbf{F}} = \vec{\mathbf{F}}_B = m\vec{\mathbf{a}}$$

Since the particle undergoes circular motion, we can treat the magnetic force as a centripetal force providing a corresponding centripetal acceleration.

$$\vec{\mathbf{F}}_B = Bq\vec{\mathbf{v}} = \frac{m\vec{\mathbf{v}}^2}{r}$$

From this equation, we can obtain various quantities.

$$r = \frac{mv}{qB} \implies \omega = \frac{qB}{m} \implies T = \frac{2\pi m}{qB}$$

16.3.3 Velocity Selector

A crossed-field velocity selector consists of a magnetic field and an electric field applied over the same region. This results in all undeflected particles passing through the region to have the same velocity.



As a charged particle enters the region, it will experience an electric force $\vec{\mathbf{F}}_E$ and a magnetic force $\vec{\mathbf{F}}_B$ simultaneously.

In order for the particle to not be deflected, it must be in equilibrium. In other words, $\vec{\mathbf{F}}_E = \vec{\mathbf{F}}_B$.

$$\vec{\mathbf{F}}_E = \vec{\mathbf{F}}_B \implies Bqv = qE$$
$$\implies v = \frac{E}{B}$$

Only particles having the speed v = E/B will pass undeflected through the crossed-field region.

- If particles move with higher velocity v, the magnetic force becomes stronger than the electric force, causing leftwards deflection.
- If particles move with lower velocity v, the magnetic force becomes weaker than the electric force, causing rightwards deflection.

16.3.4 Mass Spectrometer

Some questions may include a **mass spectrometer**, where charged particles are first sent through a velocity selector, before being shot out into a region of uniform magnetic field that causes it to move in a *semicircular path*.



The velocity of the particles after passing through the selector is v = E/B.

Upon entering the new magnetic field $\vec{\mathbf{B}}_0$, the charges undergo circular motion, moving in a semicircular of radius r before hitting a flat plane.

$$r = \frac{mv}{qB} \implies \frac{m}{q} = \frac{rB_0}{v} = rB_0\left(\frac{B}{E}\right)$$

The above result provides us with a relation between the specific charge m/q, the radius r, as well as the magnitudes of each field strength.

17 Electromagnetic Induction

17.1 Magnetic Flux

Definition 17.1: Magnetic Flux

Magnetic flux is defined as the product of an area and the component of the magnetic flux density perpendicular to that area.

$$\Phi = \mathbf{B} \cdot \mathbf{A} = BA\cos\theta$$

where Φ is the magnetic flux for a uniform magnetic flux density B at an angle θ to the normal of an area A.

The S.I. unit of magnetic flux is the *weber* (wb).

Definition 17.2: Magnetic Flux Linkage

Magnetic flux linkage is the product of the magnetic flux Φ passing through the coil and the number of turns N on the coil.

$$N\Phi = NBA\cos\theta$$

The magnetic flux linkage is simply the total magnetic flux passing through an area A bounded by a coil with N turns.

17.2 Faraday's Law

Definition 17.3: Faraday's Law

Faraday's law of electromagnetic induction states that the magnitude of the induced e.m.f. is **directly proportional** to the **rate of change** of the magnetic flux linkage.

$$|\epsilon| = \frac{d(N\Phi)}{dt} = \frac{d(NBA\cos\theta)}{dt}$$

Example 17.1

A rod of length l moves at a constant speed of v perpendicular to a magnetic field of flux density B. Use Faraday's law to determine the e.m.f. induced across the ends of the wire.



Example 17.2

A disc of area A perpendicular to the uniform magnetic field is rotated with a constant frequency f. Determine the e.m.f. induced between the centre and the rim of the disc.

We can regard the disc as a many-spoked wheel, where the radius of the disc sweeps through the magnetic field.

$$|\epsilon| = \frac{\Delta(NBA\cos\theta)}{\Delta t} = B\frac{\pi r^2}{T}$$
$$= B\pi r^2 f$$

17.3 Lenz's Law

Definition 17.4: Lenz's Law

Lenz's law states that the induced current is in a direction so as to produce effects which oppose the change in the magnetic flux.

$$\epsilon = -\frac{d(NBA\cos\theta)}{dt}$$

In a sense, the induced current flows in such a way that it attempts to preserve the original magnetic flux. If the magnetic flux is decreasing, the induced current flows to increase it. If the magnetic flux is increasing, the induced current flows to decrease it.

Considering the slidewire generator shown in Example 17.1, as the rod moves outwards, the magnetic flux directed into the area enclosed by the circuit *increases with time*.

Due to Lenz's law, the induced current flows to oppose this change. It must produce a field *directed* out of the page. Hence, the induced current must be directed *counterclockwise* when the rod moves to the right.

Similarly, the following figure shows the flow of induced current when a bar magnet moves towards

and away from a conducting loop.



17.4 Motional Electromotive Force

Motional e.m.f. refers to the electromotive force induced in a conductor that moves through a constant magnetic field.

Consider a straight current-carrying conductor of length ℓ moving uniformly with velocity \vec{v} in a direction perpendicular to a magnetic field \vec{B} .

The electrons in the conductor experience a force $\vec{\mathbf{F}}_b = \vec{\mathbf{B}} \times q\vec{\mathbf{v}}$ directed along the length of the conductor — electrons thus accumulate at one end of the conductor, **creating an electric field** $\vec{\mathbf{E}}$ inside the conductor.



In order for the velocity to remain constant, the forces must balance.

$$qE = Bvq \implies E = vB$$

The magnitude of the electric field produced in the conductor is related to the potential difference across its ends, where $\Delta V = E\ell$. This gives

$$\Delta V = E\ell = B\ell v$$

Hence, a **potential difference is maintained** as long as the conductor continues to move across the field and "cut through" the magnetic flux.

17.5 Generators

The **alternating-current generator** is a loop of wire that rotates due to the magnetic force exerted on it by a magnetic field.



As the loop rotates, the magnetic flux Φ changes with time, which induces an electromotive force and a current. Assuming that the generator rotates with constant angular speed ω ,

$$\Phi = BA\cos\theta = BA\cos\omega t$$

The induced electromotive force in the coil is thus

$$\epsilon = -\frac{d(N\Phi)}{dt} = -NBA\frac{d}{dt}(\cos\omega t)$$
$$= NBA\ \omega\sin\omega t$$

The electromotive force **varies sinusoidally** with time. The maximum electromotive force has the value $NBA\omega$, when ωt is either 0° or 180° — that is, when $\vec{\mathbf{B}}$ is perpendicular to the plane of the coil.

Example 17.3

The coil in an AC generator consists of 8 turns of wire, each of area $A = 0.09 \text{ m}^2$. The coil rotates in a magnetic field of flux density 0.5 T at a constant frequency of 60.0 Hz. Find the maximum induced electromotive force in the coil.

The induced electromotive force is at a maximum when the magnetic field is in the plane of

the coil.

$$\epsilon = \frac{d(N\phi)}{dt} \implies \epsilon_{\max} = NBA \ \omega$$
$$\implies \epsilon_{\max} = 8(0.50)(0.09) \times (2\pi)(60) = \boxed{136 \text{ V}}$$

17.6 Eddy Currents

If a solid plate conductor is subjected to a changing magnetic flux, **eddy currents** will flow simultaneously along many different paths in swirls along the conductor's plane.



In the diagram shown above, as the plate enters the magnetic field, the plate cuts the magnetic flux, which induces an e.m.f. in the plate. However, **the rate of cutting varies over the whole plate**, so different electromotive forces are induced in different parts of the plate, leading to the formation of eddy currents.

The direction of the eddy currents can be derived using Lenz"s law. For example, as the plate enters the field in the direction of $\vec{\mathbf{v}}$ shown above, the field is going into the face of the plate, hence the eddy current must provide its own magnetic field out of the page. This causes the eddy current to flow counterclockwise.

Heat energy is dissipated as eddy currents flow in the conductor.

Eddy currents can be **reduced** by eliminating paths for current flow, through

• cutting slots in the plate, or
• laminating the conductor (i.e. built up in thin layers separated by a non-conducting material such as lacquer) to prevent large current loops and confine the currents to small loops in individual layers.